



RoHS



TYPE	外殼		磁鐵 材質	環 材質	耐熱溫度	
	材質	處理				
AN-1	鋼	鍍鋅	鋁鎳鈷	黃銅	450°C	
AN-2		-				
ND-1		鍍鋅	鈹磁鐵	塑膠		80°C
ND-2		-				

品號	TYPE	D		L $^{+0.2}_{-0.2}$	K#	吸附力 (N)	質量 (g)	庫存	
		$\pm 0.2$	$h_6$						
RML-0010	AN-1	6	-	20	12	2	5	•	
RML-0012		8	-		11	4	8	•	
RML-0014		10	-		10	8.5	12	•	
RML-0016		13	-		8	12	19	•	
RML-0018		16	-		6	20	30	•	
RML-0020		20	-		5	40	58	•	
RML-0022		25	-	13	60	125	•		
RML-0024		32	-	9	160	220	•		
RML-0026		40	-	10	240	440	△		
RML-0028		50	-		400	813	△		
RML-0030		63	-		660	1306	△		
RML-0032		AN-2	-	6	10	2	2	△	
RML-0034			-	8	12	3	4	5	△
RML-0036			-	10	16	6	8.5	10	△
RML-0038	-		13	18	6	12	18	△	
RML-0040	-		16	20	6	20	30	△	
RML-0042	-		20	25	5	40	57	△	
RML-0044	-		25	30	7	60	106	△	
RML-0046	-		32	35	4	160	187	△	
RML-0048	-		40	45	5	240	390	△	
RML-0050	-		50	50	-	400	639	△	
RML-0052	-		63	60	5	660	1175	△	
RML-0054	ND-1		4	-	20	15	2.5	2	•
RML-0056			5	-			4.5	3	•
RML-0058			6	-			6	5	•
RML-0060		8	-	12			8	•	
RML-0062		10	-	24			12	•	
RML-0064		13	-	60			21	•	
RML-0066		16	-	90			31	•	
RML-0068		20	-	25			18	135	61
RML-0070		25	-	35	27	190	133	•	
RML-0072		32	-	40	32	340	249	•	
RML-0074	ND-2	-	6	10	5	6	2	△	
RML-0076		-	8	12	7	12	5	△	
RML-0078		-	10	16	11	24	9	△	
RML-0080		-	13	18	13	60	18	△	
RML-0082		-	16	20	15	90	31	△	
RML-0084		-	20	25	18	135	60	△	
RML-0086		-	25	30	22	190	115	△	
RML-0088		-	32	35	27	340	218	△	

## SP 特長

- AN-1：D公差+0.2/-0.2，AN-2：D公差 $h_6$
- ND-1：D公差+0.2/-0.2，ND-2：D公差 $h_6$
- K#是磁鐵不喪失吸附力的前提下，可以被縮短的最大尺寸

## Wa 注意

- 各種TYPE特性，請參考右上表內容
- 吸附力為單一磁鐵的測定值(參考值)

訂貨：  交期：  天    
 RML-0010  天