



TYPE	外殼.螺牙		磁鐵	耐熱溫度
	材質	處理	材質	
HF	鋼	鍍鋅	鐵氧磁鐵	200°C
SC	鋼	鍍鋅	鈷磁鐵	200°C
ND	鋼	鍍鋅	鈹磁鐵	80°C
HF-SST	SUS	-	鐵氧磁鐵	220°C

品號	TYPE	D		L		d	h	d1	l1	吸附力 (N)	質量 (g)	庫存					
RMC-0010	HF	10	+0.1 -0.1	4.5	+0.2 -0.1	M 3	5	6	7	4	3	•					
RMC-0012		13		4.5						10	4	•					
RMC-0014		16		4.5						18	6	•					
RMC-0016		20		6						30	11	•					
RMC-0018		25	+0.2 -0.1	7	+0.3 -0.1	M 4	7	8	8	40	20	•					
RMC-0020		32		7						80	31	•					
RMC-0022		40	+0.2 -0.1	8	+0.4 -0.1	M 5	9	10	+0.1 -0.1	10	125	59	△				
RMC-0024		50		10		M 6	11	12		12	220	111	△				
RMC-0026		63	+0.3 -0.1	14	+0.5 -0.1	M 8	14	15	16	350	242	△					
RMC-0028		80		18		M 10	15	20		600	500	△					
RMC-0030		100	+0.5 -0.1	22		M 12	18	22	21	900	948	△					
RMC-0032		125		26		M 14	20	25	24	1300	1732	△					
RMC-0034		SC	6	+0.1 -0.1	4.5	+0.1 -0.1	M 3	6	6	+0.1 -0.1	7	5	2	•			
RMC-0036			8		4.5							11	3	•			
RMC-0038	10		4.5		20							4	•				
RMC-0040	13		4.5		40							6	•				
RMC-0042	16		4.5	60	8	•											
RMC-0044	20		6	90	16	•											
RMC-0046	25		7	150	28	•											
RMC-0048	32		7	220	47	•											
RMC-0050	ND	6	+0.1 -0.1	4.5	+0.1 -0.1	M 3	6	6	+0.1 -0.1	7	5	2	•				
RMC-0052		8		4.5							13	3	•				
RMC-0054		10		4.5							25	4	•				
RMC-0056		13		4.5							60	5	•				
RMC-0058		16	4.5	95	7	•											
RMC-0060		20	6	140	16	•											
RMC-0062		25	7	200	27	•											
RMC-0064		32	7	350	45	•											
RMC-0066		25	+0.1 -0.1	7	+0.2 -0.2	M 4	7	8	+0.2 -0.2	8.5	32	20	•				
RMC-0068		32		7							64	31	•				
RMC-0070	HF-SST	40	+0.2 -0.1	8	+0.3 -0.1	M 5	9	8	-	9	100	56	△				
RMC-0072		50		10							175	105	△				
RMC-0074		63	+0.3 -0.1	14						+0.4 -0.1	+0.5 -0.1	8	-	8.5	280	228	△

Wa 注意

• 吸附力為單一磁鐵的測定值(參考值)

訂貨： 交期： 天 ·
RMC-0010 天 △

SD 特長

• 不銹鋼的導磁性較鋼材低，因此吸附力也較低