



Type	本體		銷子			彈簧	螺絲
	材質	處理	材質	顏色	硬度		
SJS	S45C	染黑	S45C	銀	HRC 36~45	SWP	綠(底部)
SJL				黑			-
SJH							
SJX							

Type	品號		C		D	L		SJS	SJL	SJH	SJX	專用 扳手	庫存			
	M-S	M×P	SJS SJL SJH	SJX		SJS SJL SJH	SJX	極輕荷重 最小~最大 N	輕荷重 最小~最大 N	重荷重 最小~最大 N	極重荷重 最小~最大 N		SJS	SJL SJH	SJX	
○SJS (極輕荷重)	※3-1.5○	M3×0.5	10	15	1.1	10	15	0.05~0.32	0.5~1	0.8~3	2~5	一字型 起子	•	•	•	
	※3-3○		15	20		15	20	0.09~0.32	0.3~1	0.8~3	2~5		•	•	•	
	※4-2○	M4×0.7	15	24	1.6	15	24	0.23~0.65	1~2	3~9	5~13	SJG1	•	•	•	
	※4-4○		24	24		24	24	0.24~0.65	0.6~2	2~9	5~13		•	•	•	
	※5-3○	M5×0.8	20	27	2.0	20	27	0.74~2.95	2~10	5~20	9~25	SJG1	•	•	•	
	※5-5○		27	39		27	39	0.72~2.95	2~10	3~20	9~25		•	•	•	
	※6-3○	M6×1	25	30	2.5	25	30	0.85~3.2	6~10	8~30	14~39	SJG1	•	•	•	
	※6-5○		30	36		30	36	0.85~3.2	2~10	5~30	14~39		•	•	•	
	6-10		30	-		39	-	-	1.4~10	5~28	-					
	※8-3○	M8×1.25	25	27	3.1	25	27	0.9~3.3	6~10	15~30	15~41	SJG2	•	•	•	
	※8-5○		27	30		27	35	0.9~3.3	3~10	8~30	15~41		•	•	•	
	8-10		30	-		43	-	-	3~10	7~30	-					
	※10-5○	M10×1.5	30	30	3.8	30	35	1.9~4.7	6~15	9~50	16~63	SJG2	•	•	•	
	※10-10○		30	30		43	53	1.7~4.7	3~15	8~50	13~63		•	•	•	
	※10-15		30	-		58	-	-	3~15	6~50	-					
	○SJS (輕荷重)	※12-5○	M12×1.75	30	35	5.5	30	43	1.5~4.7	6~15	19~50	37~98	SJG3	•	•	•
	※12-10○	35		35	43		58	1.3~5.9	3~20	8~50	15~98	•		•	•	
	※12-15○		35	35		51	78	1.6~5.9	3~20	5~50	15~98					
	SJL (輕荷重)	12-20		35	-		78	-	-	3.5~20	7~50	-				
	SJH (重荷重)	※16-10○	M16×2	35	35	8.0	60	60	1.7~12.8	6~40	13~80	24~147	SJG4	•	•	•
		※16-15○		35	35		60	70	1.7~12.8	4~40	13~80	22~147		•	•	•
	※SJX (極重荷重)	※16-20○	M16×2	35	35	8.0	85	90	1.7~12.8	5~40	10~80	13~147	SJG4	•	•	•
		16-30		35	35		125	125		3~40	7~80	20~147		•	•	•
		16-40		35	-		125	-	-	5~40	7~80	-				
		16-50		35	-		155	-	-	20~50	30~80	-				
		16-60		35	-		159	-	-	3~50	4~80	-				
		16-70		35	-		185	-	-	3.5~50	5.6~80	-				
		16-80		35	-		185	-	-	20~50	30~95	-				
		20-15	M20×2.5	45	-	10.0	60	-	-	13~80	25~150	-				
		20-20		45	-		72	-	12~80	23~150	-					
20-30		45		-	96		-	12~80	23~150	-						
20-40	45	-		120	-		12~80	23~150	-							
24-7	M24×3	45	-	10.0	60	-	-	20~98	44~196	-						
24-15		45	-		60	-	20~98	47~216	-							
24-20		45	-		75	-	18~98	44~216	-							
24-30		45	-		100	-	18~98	44~216	-							
24-40		45	-		124	-	-	18~98	44~216	-						
30-15	M30×3.5	45	-	14.0	66	-	-	28~118	44~275	-						
30-20		45	-		78	-	28~118	53~275	-							
30-30		45	-		100	-	28~118	45~275	-							
30-40		45	-		123	-	28~118	47~275	-							

PS. 備註

- 防鬆處理是將結合劑和硬化劑分別包裝在微膠囊內，在鎖附時擠破微膠囊，發生化學反應後，達成防鬆之功效
- 防鬆處理在鎖附後，至少靜置24小時，可獲得最佳防鬆效果
- 一旦退鎖後，防鬆處理立即失效，重新鎖附時，請額外使用厭氧膠進行接著
- M5~M30牙部耐落防鬆處理，不易鬆脫
- 經濟型產品

WA. 注意

- 專用扳手請參閱SJG
- 1N=0.101972kgf

訂貨： 交期： 天

SJS3-1.5