



本體		彈簧
材質	處理	材質
鋼	鍍鍍	SUS301
SUS304	-	




圖 1




圖 2
(尖頭)





圖 3
(圓頭)

品號	備註	A ±0.05	B	C	D	E	F	行程 s	荷重(N)		彈簧係數 N/mm	質量 (g)	庫存
									F1 ≈	F2 ≈			
22100.0012	鋼 圖 1	2.2	16	7.8	12.0	10.5	-	1.5	2.2	3.0	0.53	0.13	•
22100.0016		2.6	8	3.8	6.5	5.2	-	1.3	1.1	2.0	0.70	0.07	•
22100.0022		3.0	12	6.0	9.0	8.7	-	0.3	6.2	6.8	2.0	0.18	•
22100.0024			16	8.5	12.0	10.7	-	2.3	4.8	8.4	1.6	0.23	•
22100.0034		3.4	12	6.0	9.0	7.8	-	1.2	5.0	7.0	1.69	0.18	•
22100.0036			15	7.3	12.0	8.2	-	3.8	5.9	13.3	1.95	0.23	•
22100.0042		4.0	14	8.0	12.0	9.0	-	3.0	5.0	12.3	2.45	0.41	•
22100.0052		5.0	16	8.0	13.0	10.4	-	2.6	8.0	15.0	2.7	0.59	•
22100.0124	不銹鋼 圖 1	3.0	16	8.0	13.0	10.6	-	2.4	4.8	8.6	1.6	0.22	•
22100.0137		3.6	18	9.0	15.0	11.5	-	1.5	6.7	14.5	2.24	0.36	•
22100.0144		4.0	16	7.5	13.0	11.4	-	1.6	8.0	12.3	2.7	0.37	•
22100.0212	鋼 圖 2	2.2	16	7.8	12.0	10.5	-	1.5	2.2	3.0	0.53	0.12	•
22100.0222		3.0	11	5.0	9.0	6.7	-	2.3	1.6	3.4	0.78	0.11	•
22100.0224			16	8.5	13.0	10.7	-	2.3	4.8	8.4	1.6	0.23	•
22100.0373	不銹鋼 圖 3	3.0	13	7.0	10.0	8.9	4.1	1.1	5.3	7.2	1.75	0.19	•

Wa) 注意

- ・使用溫度max.250°C
- ・1N=0.101972kgf

Ex) 使用例



訂貨： 交期： 天

22100.0012