


本體		彈簧		銷子	
材質	處理	材質	材質	材質	處理
鋼	染黑	SUS	鋼	鋼	硬化、染黑

無耐落 品號	庫存	有耐落 品號	庫存	備註	A	螺紋規格	B	C	D	WS	荷重(lbs)		質量 (oz)
											F1 ≈	F2 ≈	
2B030.0033	•	2B030.0233	•	中荷重	6-32	2A-UNC	0.046	17/32	0.063	1/16	0.5	1.5	0.025
2B030.0036	•	2B030.0236	•		8-32		0.070	5/8	0.094	5/64	0.8	2.3	0.042
2B030.0040	•	2B030.0240	•		10-32	2A-UNF	0.093	3/4	0.125	3/32	1.4	2.7	0.063
2B030.0042	•	2B030.0242	•		1/4-20	2A-UNC	0.119	1	0.188	1/8	1.0	4.0	0.134
2B030.0044	•	2B030.0244	•			1/4-28							2A-UNF
2B030.0046	•	2B030.0246	•		5/16-18	2A-UNC	0.135	1 1/8	0.250	5/32	1.5	4.5	0.205
2B030.0048	•	2B030.0248	•		3/8-16		0.186						3/16
2B030.0050	•	2B030.0250	•		1/2-13	2A-UNC	0.248	1 1/4	0.313	1/4	2.7	9.3	0.656
2B030.0052	•	2B030.0252	•		5/8-11		0.310	1 1/2					5/16
2B030.0053	•	2B030.0253	•		3/4-10	2A-UNC	0.374	1 3/4	0.50	3/8	5.5	14.5	2.152
2B030.0054	•	2B030.0254	•		1-8		0.499	2 13/32					4.0
2B030.0063	•	2B030.0263	•		重荷重	6-32	2A-UNC	0.046	17/32	0.063	1/16	1.5	3.4
2B030.0066	•	2B030.0266	•	8-32		0.070		5/8	0.094	5/64	2.6	6.6	0.042
2B030.0070	•	2B030.0270	•	10-32		2A-UNF	0.093	3/4	0.125	3/32	3.2	9.0	0.067
2B030.0072	•	2B030.0272	•	1/4-20		2A-UNC	0.119	1	0.188	1/8	3.1	10.1	0.134
2B030.0074	•	2B030.0274	•			1/4-28							2A-UNF
2B030.0076	•	2B030.0276	•	5/16-18		2A-UNC	0.135	1 1/8	0.250	5/32	3.0	15.0	0.207
2B030.0078	•	2B030.0278	•	3/8-16			0.186						3/16
2B030.0080	•	2B030.0280	•	1/2-13		2A-UNC	0.248	1 1/4	0.313	1/4	6.6	16.0	0.649
2B030.0082	•	2B030.0282	•	5/8-11			0.310	1 1/2					5/16
2B030.0083	•	2B030.0283	•	3/4-10		2A-UNC	0.374	1 3/4	0.50	3/8	6.7	33.0	2.187
2B030.0084	•	2B030.0284	•	1-8			0.499	2 13/32					16.0

Wa) 注意


- ・無耐落使用溫度-30°C~+250°C
有耐落使用溫度-30°C~+ 90°C
- ・1lbs=4.45N
- ・中荷重定位珠牙部無雷射線



- ・重荷重定位珠牙部有兩條雷射線



Ex. 使用例



訂貨： 交期： 天

2B030.0033