



本體	把手	銷子	
材質	材質	材質	處理
SUS303	SUS303	SUS303	鍍鍍

品號	備註	A -0.02 -0.04	B	C	D ≈	E	F	G MIN.	H MIN.	WS	荷重(N)		質量 g	庫存
											F <sub>1</sub> ≈	F <sub>2</sub> ≈		
22120.0615	分割 定位柱	5	M10×1	21	51.0	17	5	5	15	12	6.0	14	43.0	・
22120.0616		6	M12×1.5	25	61.0	20	6	6	17	14	5.5	13	71.0	・
22120.0618		8	M16×1.5	31	75.5	26	8	7	23	19	11.5	28	144.0	・
22120.0620		10	M20×1.5	31	91.0	33	10	10	30	22	28.0	54	202.0	・
22120.0515	螺帽	-	M10×1	-	-	-	-	-	-	-	-	-	5.2	・
22120.0516		M12×1.5	-	-	-	-	-	-	-	-	-	-	7.4	・
22120.0518		M16×1.5	-	-	-	-	-	-	-	-	-	-	18.0	・
22120.0520		M20×1.5	-	-	-	-	-	-	-	-	-	-	32.0	・

**SP. 特長**

- 把手部上拉，銷子內縮，定位解除。手放鬆後，銷子由內藏彈簧自動回位，是一種手操作的定位柱

訂貨： 交期：   
22120.0615

**PS. 備註**

- 螺帽22120需另外購買

**EX. 使用例**

