



本體			入子	
材質	處理	抗拉強度等級	材質	耐溫
鋼	鍍鋅,藍鈍	5	PA	90°C

Type	d <sub>1</sub> 6H	d <sub>2</sub>	d <sub>3</sub>	b	h	m	槽數量	DIN 1810型 C型扳手	庫存		
SGR1804.1	M10×0.75	18	15	3	7.5	4.5	4	A 16 - 20	•		
	M10×1				7.6	4.4			•		
	M12×1	21	18		7.5	4.5			•		
	M12×1.5				9.2	5.7			•		
	M14×1.5	24	21	4	10.7	6.0		A 25 - 28	•		
	M15×1				8.5	5.5			•		
	M16×1.5				10.7	6.0			•		
	M17×1				8.5	5.5			•		
	M18×1.5	10.7	7.3		•						
	M20×1	32	27		5	9.5			6.5	A 30 - 32	•
	M20×1.5					9.6			6.0		•
	M22×1.5	38	33		5	12.7			7.0	A 40 - 42	•
	M24×1.5			10.7		6.2		•			
	M25×1.5			10.5		6.5		•			
	M28×1.5			44		38		11.2	6.9		A 45 - 50
	M30×1.5	11.0	6.5					•			
	M32×1.5	11.2	6.6					•			
	M35×1.5	50	44	11.0		7.0		•			
	M38×1.5			12.2		6.6		A 52 - 55	•		
	M40×1.5			12.0		8.2			•		
	M42×1.5	62	55	6		15.2		10.6	A 58 - 62	△	
	M45×1.5					12.0		8.2		△	
	M50×1.5					13.0		8.5		△	
	M55×2	75	68		A 68 - 75	△					
M60×2	80	73	△								
			7		13.5		6	A 80 - 90	△		

### Sp. 特長

- 此產品帶有PA入子，故具有自鎖功能，也可用作一般固定螺帽，可重複使用
- 螺紋規格相當於DIN 981滾輪軸承帶槽鎖緊螺帽
- 上表規格涵蓋了一般機械常用尺寸

訂貨：  -  交期：  天 ·  
SGR1804.1 - M30×1.5  天 △