



本體 材質	鋼珠		嵌入材 材質
	材質	處理	
SUS304	SUS440C (HRC58)	熱處理 HRC58°±2	鐵氟龍銅網

品號 右牙	M×P	庫存	品號 左牙	M×P	庫存	B	W	D	L	O	H	A	旋角 α	球徑 øC	徑向荷重 (kgf)	質量 (g)	
						H7	+0 -0.1				+0.1 -0.4	+2 -0					F
RBM6R	M6×1	·	-	-		6	9	19	47.5	8.9	6	24	38	13	12.70	490	17
-	-		RBM10LF	M10×1.25	·	10	14	27	63.5	12.9	10	30	50	13	19.05	940	54
RBM10R	M10×1.5	·	-	-		12	16	32	72	15.4	11	35	56	13	22.23	1100	85
-	-		RBM12L	M12×1.75	·	14	19	36	81	16.8	12	37	63	15	25.40	1520	125
RBM14RF	M14×1.5	·	RBM14LF	M14×1.5	·	16	21	39	91.5	19.3	13	43	72	15	28.58	2020	170
RBM14R	M14×2	·	RBM14L	M14×2	·												
RBM16RF	M16×1.5	·	RBM16LF	M16×1.5	·												
RBM16R	M16×2	·	-	-													

**Sp. 特長**

- ・採用超耐磨襯套材料(PTFE)，免給油設計，精密無間隙，不銹鋼材質，適合酸鹼場所使用

**Wa. 注意**

- ・徑向間隙值：小於0.035
- ・軸向間隙值：小於0.05

 訂貨：  交期：  

RBM6R