

料號	型號	d		D		B		B1		r(最大)		r1(最小)		基本定格荷重(N)		基本定格荷重(kgf)		係數	容許迴轉速度	型號	尺寸(mm)				尺寸(mm)				質量(kg)
		(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	Cr	Cor	Cr	Cor	Fo	ZZ(rpm)	da min	da(2) min				db max	da(2) max	Da max	Da(2) max	Db min	ra max	rb max	Dx min	
N002700034	SS603-2RS	3	9	-	5	0.15	0.15	570	187	58	19	-	-	56000	SS603-2RS	4.2	-	4.3	-	7.8	-	7.9	0.15	0.15	-	-	1.45		
N002700086	SS604-2RS	4	12	-	4	0.2	0.2	960	345	98	35	-	-	48000	SS604-2RS	5.6	-	5.6	-	10.4	-	9.9	0.2	0.2	-	-	2.29		
N002700042	SS605-2RS	5	14	-	5	-	-	1330	505	135	52	-	-	40000	SS605-2RS	6.6	-	6.9	-	12.4	-	12.2	0.2	0.2	-	-	3.48		
N002700094	SS606-2RS	6	17	-	6	-	-	2260	835	231	85	-	-	38000	SS606-2RS	8	-	8.2	-	15	-	14.8	-	-	-	-	6.08		
N002700056	SS607-2RS	7	19	-	7	0.3	0.3	2340	885	238	90	-	-	36000	SS607-2RS	9	-	9.1	-	17	-	16.5	0.3	0.3	-	-	7.51		
N002700108	SS608-2RS	8	22	-	7	-	-	3300	1370	335	140	-	-	34000	SS608-2RS	10	-	10.5	-	20	-	19	-	-	-	12.2			
N002700067	SS609-2RS	9	24	-	7	-	-	3350	1430	340	146	-	-	32000	SS609-2RS	11	-	12	-	22.8	-	20.5	-	-	-	14.7			
N002700053	SS623-2RS	3	10	-	4	0.15	0.15	630	218	64	22	-	-	50000	SS623-2RS	4.2	-	4.3	-	8.8	-	8	0.15	0.15	-	-	1.66		
N002700058	SS624-2RS	4	13	-	5	0.2	0.2	1300	485	133	49	-	-	40000	SS624-2RS	5.6	-	6	-	11.4	-	11.3	0.2	0.2	-	-	3.04		
N002700106	SS625-2RS	5	16	-	5	-	-	1730	670	177	68	-	-	36000	SS625-2RS	7	-	7.5	-	14	-	13.8	-	-	-	4.86			
N002700065	SS626-2RS	6	19	-	5	0.3	0.3	2340	885	238	90	-	-	32000	SS626-2RS	8	-	8.5	-	17	-	16.5	-	-	-	7.94			
N002700118	SS627-2RS	7	22	-	7	-	-	3300	1370	335	140	-	-	30000	SS627-2RS	9	-	10.5	-	20	-	19	0.3	0.3	-	-	12.9		
N002700028	SS628-2RS	8	24	-	8	-	-	3350	1430	340	146	-	-	28000	SS628-2RS	10	-	12	-	22	-	20.5	-	-	-	17.4			
N002700079	SS629-2RS	9	26	-	8	0.6	0.6	4550	1970	465	201	-	-	-	SS629-2RS	11	-	12.8	-	24	-	22.8	-	-	-	19.3			
N002700114	SS633-2RS	3	13	-	5	0.2	0.2	1300	485	133	49	-	-	40000	SS633-2RS	4.6	-	6	-	11.4	-	11.3	0.2	0.2	-	-	3.33		
N002700039	SS634-2RS	4	16	-	5	-	-	1730	670	177	68	-	-	36000	SS634-2RS	6	-	7.5	-	14	-	13.8	-	-	-	5.21			
N002700090	SS635-2RS	5	19	-	6	0.3	0.3	2340	885	238	90	-	-	32000	SS635-2RS	7	-	8.5	-	17	-	16.5	0.3	0.3	-	-	8.34		
N002700052	SS636-2RS	6	22	-	7	-	-	3300	1370	335	140	-	-	30000	SS636-2RS	8	-	10.5	-	20	-	19	-	-	-	14			
N002700055	SS683-2RS	3	7	-	3	0.1	0.1	390	130	40	13	-	-	63000	SS683-2RS	3.8	-	4	-	6.2	-	6.4	0.1	0.1	-	-	0.45		
N002700092	SS684-2RS	4	9	-	4	-	-	640	225	65	23	-	-	53000	SS684-2RS	4.8	-	5.2	-	8.2	-	8.1	-	-	-	1.01			
N002700044	SS685-2RS	5	11	-	-	0.15	0.15	715	281	73	29	-	-	45000	SS685-2RS	6.2	-	6.2	-	9.8	-	9.9	-	-	-	1.96			
N002700081	SS686-2RS	6	13	-	-	-	-	1080	440	110	45	-	-	40000	SS686-2RS	7.2	-	7.4	-	11.8	-	11.7	0.15	0.15	-	-	2.69		
N002700031	SS687-2RS	7	14	-	5	-	-	1170	510	120	52	-	-	-	SS687-2RS	8.2	-	8.5	-	12.8	-	12.7	-	-	-	2.97			
N002700073	SS688-2RS	8	16	-	-	0.2	0.2	1610	710	164	73	-	-	36000	SS688-2RS	9.6	-	10.2	-	14.4	-	14.2	0.2	0.2	-	-	4.02		
N002700116	SS689-2RS	9	17	-	-	-	-	1330	665	136	68	-	-	-	SS689-2RS	10.6	-	11.5	-	15.4	-	15.2	-	-	-	4.43			
N002700119	SS693-2RS	3	8	-	-	0.15	0.15	560	179	57	18	-	-	60000	SS693-2RS	4.2	-	4.3	-	6.8	-	7.3	0.15	0.15	-	-	0.83		
N002700064	SS694-2RS	4	11	-	4	-	-	960	345	98	35	-	-	48000	SS694-2RS	5.2	-	5.6	-	9.8	-	9.9	-	-	-	1.75			
N002700033	SS695-2RS	5	13	-	-	0.2	0.2	1080	430	110	44	-	-	43000	SS695-2RS	6.6	-	6.6	-	11.4	-	11.2	0.2	0.2	-	-	2.5		
N002700074	SS696-2RS	6	15	-	5	-	-	1730	670	177	68	-	-	40000	SS696-2RS	7.6	-	7.9	-	13.4	-	13.3	-	-	-	3.72			
N002700051	SS697-2RS	7	17	-	5	-	-	1610	710	164	73	-	-	36000	SS697-2RS	9	-	10.2	-	15	-	14.8	-	-	-	5.12			
N002700089	SS698-2RS	8	19	-	6	0.3	0.3	2240	910	228	93	-	-	-	SS698-2RS	10	-	10	-	17	-	16.5	0.3	0.3	-	-	7.18		
N002700061	SS699-2RS	9	20	-	6	-	-	1720	840	175	86	-	-	34000	SS699-2RS	11	-	12	-	18	-	17.2	-	-	-	8.33			
N002700035	SS6000-2RS	10	26	-	8	-	-	4550	1970	465	201	12.4	-	30000	SS6000-2RS	-	12	-	-	13	-	24	-	-	-	0.018			
N002700083	SS6001-2RS	12	28	-	-	0.3	-	5100	2370	520	241	13	-	28000	SS6001-2RS	-	14	-	-	15.5	-	26	0.3	-	-	19	0.022		
N002700041	SS6002-2RS	15	32	9	-	-	-	5600	2830	570	289	13.9	-	24000	SS6002-2RS	-	17	-	-	19	-	30	-	-	-	0.031			
N002700095	SS6003-2RS	17	35	10	-	-	-	6000	3250	610	330	14.4	-	22000	SS6003-2RS	-	19	-	-	21.5	-	33	-	-	-	0.041			
N002700101	SS6004-2RS	20	42	-	-	0.6	-	9400	5000	955	510	13.8	-	18000	SS6004-2RS	-	24	-	-	25.5	-	38	-	-	2.9	0.068			
N002700062	SS6005-2RS	25	47	-	12	-	-	10100	5850	130	595	14.5	-	15000	SS6005-2RS	-	29	-	-	30	-	43	0.6	-	-	-	0.079		
N002700115	SS6006-2RS	30	55	13	-	-	-	13200	8300	1350	845	14.7	-	13000	SS6006-2RS	-	35	-	-	36.5	-	50	-	-	-	0.116			
N002700072	SS6007-2RS	35	62	14	-	1	-	160	10300	1630	150	14.8	-	11000	SS6007-2RS	-	40	-	-	41.5	-	57	1	-	-	3.4	0.151		
N002700076	SS6008-2RS	40	68	15	-	-	-	16800	11500	1710	1180	15.3	-	10000	SS6008-2RS	-	45	-	-	47.5	-	63	-	-	-	0.19			
N002700037	SS6009-2RS	45	75	-	-	0.6	-	20900	15200	2140	1550	15.3	-	9000	SS6009-2RS	-	50	-	-	53.5	-	70	-	-	3.8	0.241			
N002700112	SS6010-2RS	50	80	-	16	-	-	21800	16600	2220	1700	15.6	-	8500	SS6010-2RS	-	55	-	-	58.5	-	75	-	-	-	0.261			
N002700069	SS6011-2RS	55	90	-	18	1.1	-	28300	21200	2880	2170	15.3	-	7500	SS6011-2RS	-	61.5	-	-	64	-	83.5	1	-	5	0.381			
N002700098	SS6012-2RS	60	95	-	-	-	-	29500	23200	3000	2370	15.6	-	7100	SS6012-2RS	-	66.5	-	-	69	-	88.5	-	-	-	0.412			
N002700107	SS6200-2RS	10	30	9	-	0.6	-	5100	2390	520	244	13.2	-	24000	SS6200-2RS	-	14	-	-	16	-	26	-	-	-	0.032			
N002700066	SS6201-2RS	12	32	10	-	-	-	6800	3050	695	310	12.3	-	22000	SS6201-2RS	-	16	-	-	17	-	28	0.6	-	-	2.9	0.037		
N002700120	SS6202-2RS	15	35	11	-	-	-	7650	3750	780	380	13.2	-	20000	SS6202-2RS	-	19	-	-	20.5	-	31	-	-	-	0.045			
N002700032	SS6203-2RS	17	40	12	-	1	-	9550	4800	975	490	13.1	-	17000	SS6203-2RS	-	21	-	-	23.5	-	36	-	-	-	0.067			
N002700084	SS6204-2RS	20	47	14	-	-	-	12800	6600	1300	670	13.1	-	15000	SS6204-2RS	-	25	-	-	26.5	-	42	-	-	-	0.107			
N002700045	SS6205-2RS	25	52	15																									