



3 Type

- A** With socket cap screw DIN 912
- B** With adjustable hand lever

1 **2**

d ₁ Clamping Ø	d ₂ Clamping Ø	d ₃	d ₄	l ₁	l ₂	l ₃	l ₄	l ₅	m
8	8	M 6	28	33	35	45	14	5	13
10	10	M 8	32	45	45	63	20	5	15
12	12	M 8	36	47	45	63	21	5	17
14	14	M 8	46	57	55	78	25,5	6	20
15	15	M 10	46	57	55	78	25,5	6	21
16	16	M 10	46	57	55	78	25,5	6	22
18	18	M 10	56	63	55	78	28,5	6	24
20	20	M 10	56	65	55	78	28,5	8	28

Specification

- Aluminum
 - Matte, tumbled ● **MT**
 - Powder coated ● **SW**
 - Black, RAL 9005, textured finish
- Stainless steel precision casting ● **NI**
 - AISI CF-8
 - Matte shot-blasted
- Socket cap screws DIN 912
Stainless steel AISI 304
- Hex nuts DIN 934
Stainless steel AISI 304
- Adjustable hand lever
 - Zinc die casting (for MT / SW)
Powder coated
Silver, RAL 9006, textured finish
 - Stainless steel precision casting (for NI)
AISI CF-8
Matte shot-blasted
 - Insert / distance bushing
Stainless steel AISI 303
- [Stainless Steel Characteristics](#) → Page 2166
- [RoHS](#)

4

Information

Swivel clamp connector joints GN 490 clamp the rods or tubes via a prism, allowing a greater Ø tolerance to be bridged. The pressure spring makes clamping and releasing easier.

see also...

- [Two-Way Clamp Mountings GN 474](#) → Page 1791
- [Twistable Two-Way Clamp Mountings GN 475](#) → Page 1792
- [Base Plate Clamp Mountings GN 473](#) → Page 1789
- [Retaining Rods / Retaining Tubes GN 480.1](#) → Page 1833

How to order (Aluminum)

GN 490-14-14-A-SW

- 1** d₁
- 2** d₂
- 3** Type
- 4** Finish

How to order (Stainless steel)

GN 490-10-10-A-NI

- 1** d₁
- 2** d₂
- 3** Type
- 4** Material