



| 1 | 2 | 3 | | | | d ₂ | h ₁ | h ₂ ≈ |
|----------------|----------------|----------------|----|----|----|----------------|----------------|------------------|
| l ₁ | d ₁ | l ₂ | | | | | | |
| 45 | M 6 | 20 | - | - | - | 10 | 9 | 34 |
| 63 | M 6 | 20 | - | - | - | 10 | 12 | 44 |
| 63 | M 8 | 25 | 30 | 35 | 50 | 13 | 12,5 | 42 |
| 78 | M 8 | 25 | 30 | 35 | 50 | 13 | 15 | 52 |
| 78 | M 10 | 35 | 50 | 55 | 60 | 16 | 16 | 50 |
| 92 | M 10 | 35 | 50 | 55 | 60 | 16 | 16 | 60 |

Specification

- Handle
Zinc die casting
Powder coated
Silver, RAL 9006, textured finish **SR**
- Threaded insert and retaining screw
Stainless steel AISI 303
- *Stainless Steel Characteristics* → Page 2166
- **RoHS**



Information

Adjustable hand levers GN 911 replace the socket cap screws DIN 912 of the tube clamp connectors and linear actuator connectors.

The table of dimensions of the tube clamp connectors and linear actuator connectors shows the matching hand lever for each screw location.

How to order

GN911-63-M8-30-SR

| | |
|---|----------------|
| 1 | l ₁ |
| 2 | d ₁ |
| 3 | l ₂ |
| 4 | Color |