



1	2	3	Hand lever with threaded stud			
l_1	d_1	l_2	d_2	h_1	$h_2 \approx$	
45	M 6	20	10	9	34	
63	M 6	20	10	12	44	

1	2	Hand lever with threaded bushing				
l_1	d_3	l_2	d_2	h_1	$h_2 \approx$	
63	M 8	-	-	-	45	
78	M 8	-	-	-	54	
78	M 10	-	-	-	54	
92	M 10	-	-	-	64	

Specification

- Handle
Stainless steel
Precision casting AISI CF-8
Matte shot-blasted **GS**
- Threaded insert and retaining screw
Stainless steel AISI 303
- *Stainless Steel Characteristics* → Page 2166
- RoHS

Information

Adjustable stainless steel hand levers GN 911.3 replace the socket cap screws DIN 912 or the cap nuts DIN 917 of the tube clamp connectors and linear actuator connectors in stainless steel.

The table of dimensions of the tube clamp connectors and linear actuator connectors shows the matching hand lever for each screw location.

How to order (Threaded bushing)		1	l_1
GN 911.3-63-M8-GS		2	d_3
		4	Finish

How to order (Threaded stud)		1	l_1
GN 911.3-45-M6-20-GS		2	d_1
		3	l_2
		4	Finish