



GROMMET GS-SG



| Material | Hardness | Colour |
|----------|-------------|--------|
| EPDM | 50 \pm 5° | Black |



| Item Name | D ₁ | D ₂ | D ₃ | D ₄ | t ₂ | t ₁ | E | P | Weight (g) |
|---------------|----------------|----------------|----------------|----------------|----------------|----------------|-----|-----|------------|
| GS-SG-23-P100 | 23 | 20 | 15 | 11 | 2 | 3.5 | 1.6 | 1 | 2.5 |
| GS-SG-25-P100 | 25 | 22 | 18 | 12 | | | | | 3 |
| GS-SG-27-P100 | 27 | 24 | 20 | 15 | 2.5 | 4 | 1.6 | 1 | 3.5 |
| GS-SG-29-P100 | 29 | 26 | 22 | 17 | | | | | 4.5 |
| GS-SG-31-P100 | 31 | 28 | 24 | 19 | 3 | 5 | 2.3 | 1.5 | 5 |
| GS-SG-35-P100 | 35 | 31 | 26 | | | | | | 3.2 |
| GS-SG-37-P100 | 37 | 33 | 28 | 21 | 3 | 5 | 2.3 | 1.5 | 7.5 |
| GS-SG-39-P100 | 39 | 35 | 30 | 23 | | | | | |
| GS-SG-41-P100 | 41 | 37 | 32 | 25 | 4 | 6 | 2.3 | 1.5 | 10 |
| GS-SG-43-P100 | 43 | 39 | 34 | 27 | | | | | |
| GS-SG-45-P50 | 45 | 42 | 36 | 28 | 4 | 6 | 2.3 | 1.5 | 12 |
| GS-SG-46-P50 | 48 | 44 | 38 | 30 | | | | | 15 |

● Flam retardant material (UL94V-0) available by made to order.