

MULTI-PURPOSE CAP GS-KD





- One-touch installation.
- Can be used on sheet metal and wooden board, ideal for cable grommet.
- GS-KD-380-350B can also be used for holes of concealed hinge.

[Specifications]

- Flam retardant material (UL94V-2).

[Cut Out Dimensions]



| Item Name | Material | Colour | A | B | D ₁ | d ₂ | Board Thickness |
|--------------------|----------|--------|------|------|----------------|----------------|-----------------|
| GS-KD-80-64B-P20 | PA | Black | 8 | 8 | 6.1 | 6.4 | 1.6 |
| GS-KD-95-80B-P20 | | | 9.5 | | 7.7 | 8 | |
| GS-KD-120-95B-P20 | | | 12 | 10.3 | 9.3 | 9.5 | |
| GS-KD-135-110B-P20 | | | 13.5 | | 10.9 | 11 | |
| GS-KD-146-127B-P20 | | | 14.6 | | 12.5 | 12.7 | |
| GS-KD-167-143B-P20 | | | 16.7 | | 14.1 | 14.3 | |
| GS-KD-182-159B-P20 | | | 18.2 | | 15.8 | 15.9 | |
| GS-KD-200-175B-P20 | | | 20 | | 17.3 | 17.5 | |
| GS-KD-232-190B-P20 | | | 23.2 | | 18.9 | 19 | |
| GS-KD-226-206B-P20 | | | 22.6 | | 20.4 | 20.6 | |
| GS-KD-258-222B-P20 | | | 25.8 | | 22 | 22.2 | 0.8~3.2 |
| GS-KD-305-255B-P20 | | | 30.5 | | 25.3 | 25.5 | |
| GS-KD-310-280B-P20 | | | 31 | 27.6 | 28 | | |
| GS-KD-333-301B-P20 | | | 33.3 | 30 | 30.1 | | |
| GS-KD-349-320B-P20 | | | 34.9 | 11.5 | 31.8 | 32 | |
| GS-KD-380-350B-P20 | | | 38 | | 34.9 | 35 | |
| GS-KD-427-380B-P20 | | | 42.7 | 37.9 | 38 | | |
| GS-KD-484-450B-P20 | | | 48.4 | 44.6 | 45 | | |
| GS-KD-550-510B-P20 | | | 55 | 50.6 | 51 | | |

※The item names have been changed.