

SLIDING DOOR ROLLER GS-JC135 U Type w/ Bracket

Made to Order

LOAD CAPACITY 3430~24500 N





- For wheel diameter above $\phi 75$, bearing with rubber seal (dustproof seal type) provides excellent water resistance.
- Ideal for exterior application.
- 2 bearings are used for wheel diameter above $\phi 75$, providing smooth movement even for heavy doors.
- Gap between bracket and wheel absorbs deformation and allows for smooth movement.

[Applications]

- Gates, etc.

[Application Example]



No.	Part Name	Material	Finish
①	Bracket	Steel (SPHC)	Clear Zinc Chromate
②	Wheel	Ductile Cast Iron	Black Enamel Finish
③	Bearing	-	-

Item Name	D	W	W ₁	C	E	F	H	H ₁	A	B	d	l	P	t	Load Capacity N/2 pcs	Load Capacity kg/2 pcs	Weight (kg)
GS-JC135-50H	50	20	41	7.5	6.3	5	64	60	100	33	11	70	3.2	3430	350	0.5	
GS-JC135-60H	60				9.3	6	67	58		38							4410
GS-JC135-75H	75	26	46	10.5	7.8	8	88	76.5	120	37	11	15	3.2	5880	600	1	
GS-JC135-90H	90						95.5									6860	700
GS-JC135-100H	105	28	50	14	7	8	118	93.5	145	39.5	20	35	6	7840	800	1.7	
GS-JC135-120H	120						125.5									9800	1000
GS-JC135-150H	150	43	88	27	8	10	165	137	250	60	20	35	6	19600	2000	6	
GS-JC135-200H	200	50	105		11.5	14	215	160	290	70				216	24500	2500	11