

STAINLESS STEEL SLIDING DOOR ROLLER GS-JS385 Flat Type w/o Bracket

SUS




- Non-bracket type of GS-JS375
- Bearing with rubber seal (dustproof seal type) provides excellent water resistance.
- Ideal for exterior application.
- 2 bearings are used for wheel diameter above $\phi 150$, providing smooth movement even for heavy doors.

[Applications]

- Gates, etc.


[Remarks]

- The dimension A of wheel diameter $\phi 150$ and $\phi 200$ contains the thickness of supplied washer.



[Parts Included]

- Bolt, nut, spring washer, spacer $\times 2$



No.	Part Name	Material	Finish
①	Wheel	Stainless Steel (SUS303)	-
②	Bearing	Stainless Steel (SUS440C)	
③	Bolt	Stainless Steel (SUS304)	

Item Name	D	A	B	F	F ₁	L	M	M ₁	t ₁	t ₂	Weight (kg)
GS-JS385-50F	50	24	20	10	18	40	17	M10	6	7	0.3
GS-JS385-60F	60										0.4
GS-JS385-75F	75										0.6
GS-JS385-90F	90										1
GS-JS385-110F	110	28	24	12	20	45	19	M12	7	8	1.8
GS-JS385-150F	150	43	43	20	40	75	30	M20	12	13	5.9
						92					
GS-JS385-200F	200	50	50	25				M24	14	15	11.7