

# STAINLESS STEEL SLIDING DOOR ROLLER GS-JS365 U Type w/ Bracket

**LOAD CAPACITY** 3920~27440 N

**SUS**





- Bearing with rubber seal (dustproof seal type) provides excellent water resistance.
- Ideal for exterior application.
- 2 bearings are used for wheel diameter above  $\phi 150$ , providing smooth movement even for heavy doors.
- Welding or screwing is possible for installation.

**[Applications]**

- Gates, etc.

[Application Example]



No.	Part Name	Material	Finish
①	Bracket	Stainless Steel (SUS304)	Polished※
②	Wheel	Stainless Steel (SUS303)	
③	Bearing	Stainless Steel (SUS440C)	-

※ Mirror polished for wheel diameter more than  $\phi 150$ .

Item Name	D	W	W <sub>1</sub>	A	B	C	E	F	H	H <sub>1</sub>	d	I	P	t	Load Capacity N/2 pcs	Load Capacity kgf/2 pcs	Weight (kg)
GS-JS365-50H	50	20	47	100	30	7.5	6.3	7	62	57	11	15	75	3	3920	400	0.5
GS-JS365-60H	60			67					4900						500	0.6	
GS-JS365-75H	75			87.5					6370						650	0.9	
GS-JS365-90H	90			95					11760						1200	1.2	
GS-JS365-110H	110	24	53	145	34	14	5	8	120	93.5			114		13720	1400	2
GS-JS365-150H	150	43	88	250	57	27	8	15	165	137	20	35	185	4	21560	2200	6.5
GS-JS365-200H	200	50	107	290	70		11.5	14	215	160			216	6	27440	2800	14