

# STAINLESS STEEL SLIDING DOOR ROLLER GS-JS300 V Type w/ Bracket

**LOAD CAPACITY**

**3920~27440 N**

**SUS**




- Bearing with rubber seal (dustproof seal type) provides excellent water resistance.
- Ideal for exterior application.
- 2 bearings are used for wheel diameter above  $\phi 150$ , providing smooth movement even for heavy doors.
- Welding or screwing is possible for installation.

### [Applications]


- Gates, etc.

### [Application Example]



No.	Part Name	Material	Finish
①	Bracket	Stainless Steel (SUS304)	Polished※
②	Wheel	Stainless Steel (SUS303)	
③	Bearing	Stainless Steel (SUS440C)	-

※Mirror polished for wheel diameter more than  $\phi 150$ .



Item Name	D	W	W <sub>i</sub>	A	B	C	E	F	H	H <sub>i</sub>	d	l	P	t	Load Capacity N/2 pcs	Load Capacity kgf/2 pcs	Weight (kg)
GS-JS300-50V	50	20	47	100	30	7.5	3.5	7	62	57	11	15	85	3	3920	400	0.5
GS-JS300-60V	60								67						4900	500	0.6
GS-JS300-75V	75								87.5						6370	650	0.9
GS-JS300-90V	90	24	53	145	34	10.5	4.6	8	95	76.5	20	35	185	4	11760	1200	1.2
GS-JS300-110V	110								114						13720	1400	2
GS-JS300-150V	150								43						88	250	57
GS-JS300-200V	200	50	107	290	70	15	7	20	215	160	27440	2800	13				