

PARTS SEPARABLE CASTER (W/GLIDE) GS-CAB Threaded Bolt Type







After installing the levelling glide, caster direction can be changed. Caster will not interfere with operation when its direction is set to the inside of cabinet.


- Caster with built-in levelling glide.
- Ideal for fixtures and devices without frequent movement (long fixation period).
- Two types of wheels available: Polyamide and elastomer.
- Model without levelling glide and options such as shockproof plate, rubber seat used for levelling glide are also available.

[Remarks]

Please loose the fixing screw when using as a caster.

| No. | Part Name | Material | Finish/Colour | | | | |
|-----|-----------|--------------------------|------------------------------------|--|--|--|--|
| 1 | Body | PA | Black (B)/White (W) | | | | |
| 2 | Levelling | | Coloured Zinc Chromate (Trivalent) | | | | |
| | Glide | Stainless Steel (SUS304) | Passivation* | | | | |
| 3 | Threaded | | Coloured Zinc Chromate (Trivalent) | | | | |
| | Bolt | Stainless Steel (SUS304) | Passivation* | | | | |
| 4 | Wheel | PA/Elastomer (TPE) | Black (B)/White (W) | | | | |

Passivation is a kind of surface treatment
providing rust protection for stainless steel.



| Item Name | Material | Finish/Colour | D | Н | h | Е | F | Α | В | M ₁ | Load Capacity N/pc | Load Capacity kgf/pc | Weight (g) |
|-------------|----------------------------------|-------------------------------|----|----|----|------|------|----|------|----------------|--------------------|----------------------|------------|
| GS-CABF50B | Steel, PA | Coloured Zinc Chromate, Black | 50 | | | | | 40 | | 0 M12 | 588 | 60 | 260 |
| GS-CABF50W | Steet, PA | Coloured Zinc Chromate, White | | 67 | 10 | | ., | | 70 | | | | |
| GS-CABF50UB | Steel, Elastomer | Coloured Zinc Chromate, Black | | | | 30 | ا 40 | | /0 | | | | |
| GS-CABF50UW | (TPE) | Coloured Zinc Chromate, White | | | | | | | | | | | |
| GS-CABF75B | Ctool DA | Coloured Zinc Chromate, Black | 75 | | | | | 50 | | 5 M16 | 1176 | 120 | 400 |
| GS-CABF75W | Steel, PA | Coloured Zinc Chromate, White | | 96 | 24 | 35 | 42 | | 0.5 | | | | |
| GS-CABF75UB | Steel, Elastomer | Coloured Zinc Chromate, Black | | | | | | | 80 | | | | 430 |
| GS-CABF75UW | (TPE) | Coloured Zinc Chromate, White | | | | | | | | | | | 430 |
| GS-CABS50W | Stainless Steel, PA | Passivation, White | 50 | 67 | 10 | 20 | 0.4 | 40 | 70 | M12 | 588 | 60 | 262 |
| GS-CABS50UW | Stainless Steel, Elastomer (TPE) | | | | 10 | 30 | 04 | 40 | /0 | | | | 230 |
| GS-CABS75W | Stainless Steel, PA | | 75 | 96 | 24 | O.F. | 40 | 50 | O.F. | M16 | 1176 | 120 | 402 |
| GS-CABS75UW | Stainless Steel, Elastomer (TPE) | | | | | 35 | 42 | | 80 | | | | 430 |