[Cautions]

- Do not apply excessive load on the cam and do not attempt to force the key to turn.
- · Do not attempt to turn the key unless it is fully inserted in the lock.
- Removal of the key should only be done in the locked position. Some locks also allow removal in the open position as well.
- When tightening the cam hexagonal nut, insert the key in the lock and hold the cam, in order to avoid breaking the lock pin.
- Most locks parts and made of zinc alloy or brass. Their service life might therefore be reduced when exposed to corrosive environments such as spa or seaside locations.
- We recommend a regular lubrication of the locks, using specific lubricant such as Teflon or graphite based ones.
- Please consult Sugatsune for specific key numbers and combinations before making the final key plan.




Fig.1




Fig.2

[Key Alike and Key Different]

- · Locks have two types: Key alike and key different. Key alike indicates identical key number of multiple locks. Key different indicate different key numbers of multiple locks.
- If ordering 3 locks for 3 different keys with the numbers of A, B and C, key alike will be A, A, A (or B, B, B or C, C, C), while key different will be A, B, C.
- Locks with key alike are suitable for places (like dustbins at the station) where the worker wants to unlock multiple locks with one key; While locks with key different cannot be unlocked with the same key, suitable for places (like lockers) where strict security management is required.
- For the locks herein, to differentiate the types with key alike from those with key different, the item name of a lock with key alike is suffixed with "-D", while that of a lock with key different is suffixed with "-B".
- · For key numbers and their combination, please consult us before determining specifications.

[Exclusive Number]

 Exclusive key numbers not overlapping with other customers are available depending on the products. Please consult us for made to order.

Sugatsune Also Offers Made-to-order Products! Example of Specification Change Cam shape or length change, etc. For OEM and ODM request form with required items at consultation, refer to ▶ P.923-925