
LINEAR BALL BEARING GUIDE GS-ESR9 For Light Weight







Inner member is located inside the retainer for precise movement.
Ideal for doors of small cabinets. 2 slides can support up to 5 kg.

[Remarks

- Outer member cannot be used in full stroke since the erected parts at its both ends are low in strength against strong shock and continuous movement. Install a stopper with a space from the erected part.
- Ball retainer may shift depending on inner member movement frequency and other conditions. In this case, correct by moving the inner member left or right to the end
- Retainer may shift downwards In case of moving in the vertical direction.

No.	Part Name	Material	Finish
1	Outer Member		
2	Inner Member		Plain
3	Mounting Plate	Stainless Steel (SUS304)	
4	Retainer		
(5)	Balls		_

Sold by piece.

Item Name	Slide Length	Travel Length	Α	В	С	Weight (kg/pc)
GS-ESR9-12	304.8	225		152.4	254	0.14
GS-ESR9-14	355.6	276	_	203.2	304.8	0.16
GS-ESR9-16	406.4	327		254	355.6	0.17
GS-ESR9-18	457.2	378	203.2	304.8	406.4	0.19
GS-ESR9-20	508	428	228.6	355.6	457.2	0.20
GS-ESR9-22	558.8	479	254	406.4	508	0.22
GS-ESR9-24	609.6	530	279.4	457.2	558.8	0.24
GS-ESR9-26	660.4	581	304.8	508	609.6	0.25
GS-ESR9-28	711.2	632	330.2	558.8	660.4	0.27