



名稱	材質		處理		顏色
	SGR927	SGR927.4	SGR927	SGR927.4	
把手	鋅壓鑄	鋅壓鑄	塑膠披覆	塑膠披覆	黑
螺絲·螺帽	銅	SUS303	鍍鋅	-	-
接觸面華司(圖1)	-	PA+玻纖	-	-	-
接觸面華司(圖2)	POM+玻纖	-	-	-	-





圖 2 調整式







圖 1 固定式







銅 品號	庫存	不銹鋼 品號	庫存	備註	l <sub>1</sub>	d <sub>2</sub>	l <sub>2</sub> 夾持時	b	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	h 行程90°時	l <sub>3</sub> 夾持時		l <sub>4</sub> 調整範圍	l <sub>5</sub> 夾持時	l <sub>6</sub> 夾持時	t 牙長
													min.	max.				
SGR927-010	•	SGR927.4-010	△	圖 1 固定式	63	M6×1	20	16	16	-	18.5	0.75	-	-	-	3	16.3	10
SGR927-011	•	SGR927.4-011	△				25											
SGR927-012	•	SGR927.4-012	△				30											
SGR927-013	•	SGR927.4-013	△				35											
SGR927-014	•	SGR927.4-014	△				40											
SGR927-016	•	SGR927.4-016	△		50													
SGR927-020	•	SGR927.4-020	△		82	M8×1.25	25	20	20	-	22.5	1	-	-	-	3.7	19.5	12
SGR927-021	•	SGR927.4-021	△				30											
SGR927-022	•	SGR927.4-022	△				35											
SGR927-023	•	SGR927.4-023	△				40											
SGR927-025	•	SGR927.4-025	△				50											
SGR927-027	•	SGR927.4-027	△		60													
SGR927-029	•	SGR927.4-029	△		101	M10×1.5	25	25	26	-	27	1.5	-	-	-	4.8	25.3	15
SGR927-031	•	SGR927.4-031	△				30											
SGR927-033	•	SGR927.4-033	△				35											
SGR927-035	•	SGR927.4-035	△	40														
SGR927-037	•	SGR927.4-037	△	50														
SGR927-039	•	SGR927.4-039	△	60														
SGR927-110	•	SGR927.4-110	△	圖 2 調整式	63	M6×1	20	16	16	19	-	0.75	16.3	18.8	2.5	3	-	10
SGR927-111	•	SGR927.4-111	△				25											
SGR927-112	•	SGR927.4-112	△				30											
SGR927-113	•	SGR927.4-113	△				35											
SGR927-114	•	SGR927.4-114	△				40											
SGR927-116	•	SGR927.4-116	△		50													
SGR927-120	•	SGR927.4-120	△		82	M8×1.25	25	20	20	25	-	1	19.5	22.5	3	3.7	-	12
SGR927-121	•	SGR927.4-121	△				30											
SGR927-122	•	SGR927.4-122	△				35											
SGR927-123	•	SGR927.4-123	△				40											
SGR927-125	•	SGR927.4-125	△				50											
SGR927-127	•	SGR927.4-127	△		60													
SGR927-129	•	SGR927.4-129	△		101	M10×1.5	25	25	26	30	-	1.5	25.3	29.3	4	4.8	-	15
SGR927-131	•	SGR927.4-131	△				30											
SGR927-133	•	SGR927.4-133	△				35											
SGR927-135	•	SGR927.4-135	△	40														
SGR927-137	•	SGR927.4-137	△	50														
SGR927-139	•	SGR927.4-139	△	60														

**SP** 特長

- 適用於快速夾持和拆卸工件
- 當使用圖2把手，可調整把手位置
- 耐熱溫度：80°C

調整式凸輪把手構造



$l_3$ 可用滾花輪螺母調節偏心凸輪與接觸面間的距離，並得到最大夾緊力

