









本體		螺絲		優力膠		硬度
材質	處理	材質	處理	WAT-LSCU	WAT-LSCN-U	
SS400	染黑	SCM435	染黑	WAT-SBU 15 20 25	WAT-SBUH 6 8	Shor A90
SUS304	-	SUSXM7	-			

WAT-LSCU

WAT-LSCN-U



鐵		不銹鋼		線軌 尺寸	對應廠商產品			W	H	A	B	J	P	T	M	D	附屬品 螺絲	D ₁	L
品號	庫存	品號	庫存		IKO	NSK	THK												
WAT-LSCU-01	△	WAT-LSCU-01S	△	15	-	-	SRS15M	30	22.5	12	18	35	12	M4	5.5	M5×16	15	11	
WAT-LSCU-02	△	WAT-LSCU-02S	△		LWH15	LS15AL	HSR15A	38	30.5										
WAT-LSCU-03	△	WAT-LSCU-03S	△		-	LH15AN	-	43	35.0										
WAT-LSCU-02	△	WAT-LSCU-02S	△	20	-	-	SRS20M	50	38	30.5	20	35	16	M5	6.6	M6×20	20	13	
WAT-LSCU-04	△	WAT-LSCU-04S	△		LWH20	LS20AL · LH20AN	HSR20A	45	35.0										
WAT-LSCU-05	△	WAT-LSCU-05S	△	25	-	-	SRS25M	60	40	30.0	24	45	16	M5	9.0	M8×20	25	13	
WAT-LSCU-06	△	WAT-LSCU-06S	△		LWH25	LS25AL · LH25AL	HSR25A	51	41.0										
WAT-LSCU-07	△	WAT-LSCU-07S	△	30	LWH30	LS30AL · LH30AL	HSR30A	65	57	44.5	24	45	16	M5	9.0	M8×20	25	13	
WAT-LSCU-08	△	WAT-LSCU-08S	△	35	LWH35	LS35AL · LH35AL	HSR35A	63	50.5										

鐵		不銹鋼		線軌 尺寸	對應廠商產品			W	H	A	B	J	P	T	M (細牙)	D	附屬品 螺絲
品號	庫存	品號	庫存		IKO	NSK	THK										
WAT-LSCN-01-U	△	WAT-LSCN-01S-U	△	15	-	-	SRS15M	30	23.5	12	18	35	12	M6×P0.75	5.5	M5×16	
WAT-LSCN-02-U	△	WAT-LSCN-02S-U	△		LWH15	LS15AL	HSR15A	38	31.5								
WAT-LSCN-03-U	△	WAT-LSCN-03S-U	△		-	LH15AN	-	43	35.5								
WAT-LSCN-04-U	△	WAT-LSCN-04S-U	△	20	-	-	SRS20M	50	35	27.5	20	35	16	M8×P1.0	6.6	M6×20	
WAT-LSCN-05-U	△	WAT-LSCN-05S-U	△		LWH20	LH20AN	HSR20A	45	37.5								
WAT-LSCN-06-U	△	WAT-LSCN-06S-U	△	25	-	-	SRS25M	60	40	32.5	24	45	16	M8×P1.0	9.0	M8×20	
WAT-LSCN-07-U	△	WAT-LSCN-07S-U	△		LWH25	LH25AL	HSR25A	51	43.5								
WAT-LSCN-08-U	△	WAT-LSCN-08S-U	△	30	LWH30	LS30AL · LH30AL	HSR30A	65	57	49.5	24	45	16	M8×P1.0	9.0	M8×20	
WAT-LSCN-09-U	△	WAT-LSCN-09S-U	△		LWH30	LS30AL · LH30AL	HSR30A	57	49.5								
WAT-LSCN-10-U	△	WAT-LSCN-10S-U	△	35	LWH35	LS35AL · LH35AL	HSR35A	65	57	49.5	24	45	16	M8×P1.0	9.0	M8×20	
WAT-LSCN-11-U	△	WAT-LSCN-11S-U	△		LWH35	LS35AL · LH35AL	HSR35A	63	55.5								

Ps. 備註

- L, L₂尺寸請參考WAT-SBUH
- 使用在線軌的防脫落和位置定位
- 附優力膠型可消除衝擊音量

Wa. 注意

- 以上產品是本公司自訂規格；記載之對應廠商產品，請貴客戶自行確認

訂貨： 交期： 天

WAT-LSCU-01