



底板		本體		硬度	螺栓	
材質	處理	材質	顏色		材質	處理
鋼	鍍鋅	天然橡膠 (NR)	黑	55 Shore A±5	鋼	鍍鋅
SUS304	-				SUS304	-

品號	鋼			SUS304			D	L	d	d ₁	l	最大壓縮量 (mm)	
	定數 (N/mm)	最大荷重 (N)	庫存	品號	定數 (N/mm)	最大荷重 (N)							庫存
FVJ-433001	40	80	•	FVJ-433601	40	80	•	10	8	M4	4.5	10	2
FVJ-433006	28	69	•	FVJ-433606	28	69	•	10	10	M4	8	10	2.5
FVJ-433011	41	154	•	FVJ-433611	30	113	•	15	15	M4	8.5	10	3.75
FVJ-433016	43	163	•	FVJ-433616	43	163	•	15	15	M4	12	10	3.75
FVJ-433031	73	273	•	FVJ-433631	73	273	•	20	15	M6	14	18	3.75
FVJ-433033	50	238	•	FVJ-433633	50	238	•	20	19	M6	14	18	4.75
FVJ-433035	46	231	•	FVJ-433635	46	231	•	20	20	M6	14	18	5
FVJ-433041	49	268	•	FVJ-433641	37	205	•	21	22	M6	16	18	5.5
FVJ-433021	26	194	•	FVJ-433621	37	280	•	20	30	M6	12	18	7.5
FVJ-433037	27	202	•	FVJ-433637	68	507	•	20	30	M6	14	18	7.5
FVJ-433051	177	887	•	FVJ-433651	177	887	•	25	20	M6	18	18	5
FVJ-433056	180	902	•	FVJ-433656	112	560	•	25	20	M6	20	18	5
FVJ-433066	217	1087	•	FVJ-433666	217	1087	•	30	20	M8	22	20	5
FVJ-433061	107	671	•	FVJ-433661	107	671	•	30	25	M8	18	20	6.25
FVJ-433076	559	2097	•	FVJ-433676	559	2097	•	35	15	M8	31	20	3.75
FVJ-433071	184	1564	•	FVJ-433671	184	1564	•	35	34	M8	25	20	8.5
FVJ-433085	389	2430	•	FVJ-433685	380	2430	•	40	25	M8	30	23	6.25
FVJ-433083	216	1621	•	FVJ-433683	216	1621	•	40	30	M8	25	23	7.5
FVJ-433089	250	1873	•	FVJ-433689	250	1873	•	40	30	M8	33	23	7.5
FVJ-433081	59	706	•	FVJ-433681	56	705	•	40	48	M8	20	23	12
FVJ-433087	64	795	•	FVJ-433687	64	795	•	40	50	M8	32	23	12.5
FVJ-433096	648	2430	•	FVJ-433696	648	2430	•	50	15	M10	46	28	3.75
FVJ-433091	203	1523	•	FVJ-433691	203	1523	•	50	30	M10	42	28	7.5
FVJ-433093	118	1328	•	FVJ-433693	118	1328	•	55	45	M10	44	28	11.25
FVJ-433101	109	1222	•	FVJ-433701	109	1222	•	57	45	M10	25	28	11.25
FVJ-433106	252	3785	•	FVJ-433706	252	3785	•	60	60	M10	49	28	15
FVJ-433111	160	2114	•	FVJ-433711	160	2114	•	70	53	M12	45	37	13.25
FVJ-433116	498	4170	•	FVJ-433716	498	4170	•	72	33.5	M12	64	37	8.375
FVJ-433121	361	3610	•	FVJ-433721	361	3610	•	75	40	M12	60	37	10
FVJ-433126	579	10865	•	FVJ-433726	579	10865	•	95	75	M16	80	41	18.75

SP 特長

- 用在減震和降低機件的晃動及噪音

PS 備註

- 1N=0.101972kgf
- 荷重(N)=定數(N/mm)×壓縮量(mm)
- 40 Shore A和70 Shore A可訂製
- 工作溫度=-40°C~80°C

訂貨： 交期： 天

FVJ-433001