



底板		本體		硬度	螺栓	
材質	處理	材質	顏色		材質	處理
鋼	鍍鋅	天然橡膠 (NR)	黑	55 Shore A±5	鋼	鍍鋅
SUS304	-				SUS304	-

鋼				SUS304				D	L	d	d <sub>1</sub>	l	h	最大壓縮量 (mm)
品號	定數 (N/mm)	最大荷重 (N)	庫存	品號	定數 (N/mm)	最大荷重 (N)	庫存							
FVK-433751	17	43	•	FVK-434201	46	115	•	10	10	M4	8	10	4	2.5
FVK-433761	35	132	•	FVK-434211	65	242	•	15	15	M4	8.5	10	4	3.75
FVK-433766	38	142	•	FVK-434216	69	259	•	15	15	M4	12	10	4	3.75
FVK-433773	66	247	•	FVK-434223	101	380	•	20	15	M6	14	18	6	3.75
FVK-433775	48	226	•	FVK-434225	74	353	•	20	19	M6	14	18	6	4.75
FVK-433777	45	223	•	FVK-434227	70	351	•	20	20	M6	14	18	6	5
FVK-433781	44	240	•	FVK-434231	67	369	•	21	22	M6	16	18	6	5.5
FVK-433771	20	147	•	FVK-434221	34	254	•	20	30	M6	12	18	6	7.5
FVK-433779	74	556	•	FVK-434229	47	352	•	20	30	M6	14	18	6	7.5
FVK-433791	126	631	•	FVK-434241	312	1558	•	25	20	M6	18	18	6	5
FVK-433796	131	655	•	FVK-434246	323	1615	•	25	20	M6	20	18	6	5
FVK-433806	173	863	•	FVK-434256	469	2346	•	30	20	M8	22	20	8	5
FVK-433801	82	510	•	FVK-434251	251	1570	•	30	25	M8	18	20	8	6.25
FVK-433816	349	1310	•	FVK-434266	1003	3762	•	35	15	M8	31	20	8	3.75
FVK-433811	148	1255	•	FVK-434261	332	2826	•	35	34	M8	25	20	8	8.5
FVK-433825	341	2133	•	FVK-434275	632	3952	•	40	25	M8	30	23	8	6.25
FVK-433823	146	1096	•	FVK-434273	350	2628	•	40	30	M8	25	23	8	7.5
FVK-433829	157	1178	•	FVK-434279	378	2835	•	40	30	M8	33	23	8	7.5
FVK-433821	49	583	•	FVK-434271	109	1314	•	40	48	M8	20	23	8	12
FVK-433827	49	610	•	FVK-434277	124	1546	•	40	50	M8	32	23	8	12.5
FVK-433831	443	3320	•	FVK-434281	443	3320	•	50	30	M10	42	28	10	7.5
FVK-433836	95	1066	•	FVK-434286	205	2310	•	55	45	M10	44	28	10	11.25
FVK-433841	94	1055	•	FVK-434291	184	2065	•	57	45	M10	25	28	10	11.25
FVK-433846	171	2560	•	FVK-434296	337	5060	•	60	60	M10	49	28	10	15
FVK-433851	168	2219	•	FVK-434301	285	3777	•	70	53	M12	45	37	12	13.25
FVK-433856	402	3364	•	FVK-434306	1022	8559	•	72	33.5	M12	64	37	12	8.375
FVK-433861	282	2819	•	FVK-434311	818	8176	•	75	40	M12	60	37	12	10
FVK-433866	473	8873	•	FVK-434316	828	15518	•	95	75	M16	80	41	16	18.75

**SP** 特長

- 用在減震和降低機件的晃動及噪音

訂貨：  交期：  天

FVK-433751

**PS** 備註

- 1N=0.101972kgf
- 荷重(N)=定數(N/mm)×壓縮量(mm)
- 40 Shore A和70 Shore A可訂製
- 工作溫度=-40°C~80°C