



底板		本體		硬度	螺栓	
材質	處理	材質	顏色		材質	處理
鋼	鍍鋅	天然橡膠 (NR)	黑	55 Shore A±5	鋼	鍍鋅
SUS304	-				SUS304	-

鋼		SUS304		D	L	d	d ₁	l	定數 (N/mm)	最大荷重 (N)	最大壓縮量 (mm)
品號	庫存	品號	庫存								
FVH-432001	•	FVH-432601	•	20	17	M5	10	6	96	407	4.25
FVH-432002	•	FVH-432602	•	20	17	M5	10	10	96	407	4.25
FVH-432003	•	FVH-432603	•	20	17	M5	10	20	96	407	4.25
FVH-432011	•	FVH-432611	•	20	17	M6	10	12	96	407	4.25
FVH-432012	•	FVH-432612	•	20	17	M6	10	18	96	407	4.25
FVH-432013	•	FVH-432613	•	20	17	M6	10	25	96	407	4.25
FVH-432021	•	FVH-432621	•	25	17	M6	19	8	69	293	4.25
FVH-432022	•	FVH-432622	•	25	17	M6	19	12	69	293	4.25
FVH-432023	•	FVH-432623	•	25	17	M6	19	18	69	293	4.25
FVH-432024	•	FVH-432624	•	25	17	M6	19	25	69	293	4.25
FVH-432031	•	FVH-432631	•	32	22	M8	24	10	116	638	5.5
FVH-432032	•	FVH-432632	•	32	22	M8	24	16	116	638	5.5
FVH-432033	•	FVH-432633	•	32	22	M8	24	23	116	638	5.5
FVH-432034	•	FVH-432634	•	32	22	M8	24	30	116	638	5.5
FVH-432041	•	FVH-432641	•	38	35	M8	30	10	128	1117	8.75
FVH-432042	•	FVH-432642	•	38	35	M8	30	16	128	1117	8.75
FVH-432043	•	FVH-432643	•	38	35	M8	30	30	128	1117	8.75
FVH-432051	•	FVH-432651	•	38	35	M10	30	12	128	1117	8.75
FVH-432052	•	FVH-432652	•	38	35	M10	30	20	128	1117	8.75
FVH-432053	•	FVH-432653	•	38	35	M10	30	28	128	1117	8.75
FVH-432054	•	FVH-432654	•	38	35	M10	30	40	128	1117	8.75
FVH-432061	•	FVH-432661	•	43	50	M10	30	12	122	1523	12.5
FVH-432062	•	FVH-432662	•	43	50	M10	30	20	122	1523	12.5
FVH-432063	•	FVH-432663	•	43	50	M10	30	28	122	1523	12.5
FVH-432064	•	FVH-432664	•	43	50	M10	30	40	122	1523	12.5
FVH-432071	•	FVH-432671	•	50	20	M10	40	12	462	2310	5
FVH-432072	•	FVH-432672	•	50	20	M10	40	20	462	2310	5
FVH-432073	•	FVH-432673	•	50	20	M10	40	28	462	2310	5
FVH-432074	•	FVH-432674	•	50	20	M10	40	40	462	2310	5
FVH-432081	•	FVH-432681	•	60	40	M10	40	12	209	2090	10
FVH-432082	•	FVH-432682	•	60	40	M10	40	20	209	2090	10
FVH-432083	•	FVH-432683	•	60	40	M10	40	28	209	2090	10
FVH-432084	•	FVH-432684	•	60	40	M10	40	40	209	2090	10

SP 特長

- 用在減震和降低機件的晃動及噪音

PS 備註

- 1N=0.101972kgf
- 荷重(N)=定數(N/mm)×壓縮量(mm)
- 40 Shore A和70 Shore A可訂製
- 工作溫度=-40°C~80°C

訂貨： 交期： 天

FVH-432001