

名稱	材質	處理
吊環	鍛造合金鋼	塗裝
支架	鍛造合金鋼	-
螺栓	鋼	染黑

品號	E	A	B	C	D	F	G	H	載重極限Tons		鎖緊扭矩 N · M	螺栓尺寸 M	質量 (Kg)	庫存	
									5:1	4:1					
G203-004	17	40	41	41	9	102	65	33	0.40	0.50	10	M8	0.4	△	
G203-005	11			43					0.45	0.55	16	M10	0.5	△	
*G203-005L	26			43					0.45	0.55	16	M10	0.5	△	
G203-010	15	65	58	57	15	158	105	45	1.05	1.30	38	M12	1.7	△	
*G203-010L	30			57					1.05	1.30	38	M12	1.7	△	
G203-019	20			61					1.90	2.40	81	M16	1.8	△	
*G203-019L	35			61					1.90	2.40	81	M16	1.8	△	
G203-021	25			65					2.15	2.70	136	M20	1.9	△	
*G203-021L	45			65					2.15	2.70	136	M20	1.9	△	
G203-030	25	85	73	74	22	204	134	54	3.00	3.75	637	M20	4.0	△	
*G203-030L	45			74					3.00	3.75		136	M20	5.2	△
G203-042	26			78					4.20	5.25			312	M24	4.2
*G203-042L	56			78					4.20	5.25		312	M24	4.3	△
G203-070	81	100	80	77	25	218	160	58	7.00	8.75	637	M30	6.6	△	
G203-110	76	120	106	108	36	308	220	85	11.00	13.75	1005	M36	15.0	△	
G203-125	95			111					12.50	15.60		1350	M42	16.0	△
G203-135	105			115					13.50	16.90			M48	16.0	△
G203-155	94	138	109	121	34	312	241	86	15.50	19.40	2847	M56	19.1	△	
G203-223	98			95	132			38	92	22.30		27.90	M64	23.0	△

Wa) 注意









- 可360°旋轉及180°翻轉起吊，隨任意方向調整
- 吊環採用鍛造合金鋼製作，並均經過淬火和回火處理
- 吊環製造和測試都依據歐盟規範EN1677-1相關標準實施
- 產品經100%磁粉探傷檢驗
- 所有鍛造件及六角螺栓均可以通過檢測報告來質量追溯
- 螺栓是公制螺紋
- 驗證荷載為工作極限荷載的2.5倍
- 以1.5倍工作極限荷載的作用力，進行20,000次的疲勞極限測試
- G203的起重吊環都能夠滿足或者超過美國規範ASME B30.26標準的要求
- 被吊物僅需螺孔，可用平頭/套頭扳手或內六角扳手安裝使用
- G203如無庫存，會有MOQ限制，及交期較長問題

PS) 備註

- 設計安全係數為4:1時，驗證載荷應為工作荷載極限的2.5倍
- *長螺栓設計用於軟金屬工件

訂貨： 交期： 天

G203-004

吊環安裝方式											
		1	2	1	2	2		2	3-4		3-4
起吊角度		0°	0°	90°	90°	0°-45°	45°-60°	不對稱	0°-45°	45°-60°	不對稱
品號	螺紋	載重極限 tons									
G203-004	M8	0.50	1.0	0.50	1.0	0.70	0.50	0.50	1.05	0.75	0.50
G203-005	M10	0.55	1.1	0.55	1.1	0.77	0.55	0.55	1.16	0.83	0.55
G203-010	M12	1.30	2.6	1.30	2.6	1.82	1.30	1.30	2.73	1.95	1.30
G203-019	M16	2.40	4.8	2.40	4.8	3.36	2.40	2.40	5.04	3.60	2.40
G203-021	M20	2.70	5.4	2.70	5.4	3.78	2.70	2.70	5.67	4.05	2.70
G203-030		3.75	7.5	3.75	7.5	5.25	3.75	3.75	7.88	5.63	3.75
G203-042	M24	5.25	10.5	5.25	10.5	7.35	5.25	5.25	11.03	7.88	5.25
G203-070	M30	8.75	17.5	8.75	17.5	12.25	8.75	8.75	18.38	13.13	8.75
G203-110	M36	13.75	27.5	13.75	27.5	19.25	13.75	13.75	28.88	20.63	13.75
G203-125	M42	15.60	31.2	15.60	31.2	21.84	15.60	15.60	32.76	23.40	15.60
G203-135	M48	16.90	33.8	16.90	33.5	23.66	16.90	16.90	35.49	25.35	16.90
G203-155	M56	19.40	38.8	19.40	38.8	27.16	19.40	19.40	40.74	29.10	19.40
G203-223	M64	27.90	55.8	27.90	55.8	39.06	27.90	27.90	58.59	41.85	27.90