



1.1
1.2
1.3
1.4
2.1

1			2			3									
d ₁	d ₂		l ₁			d ₃	h ₁	h ₂	h ₃	h ₄ Stroke	l ₂				
14	M 5	M 6	12	16	20	25	32	40	50	10	25	4,5	35	3,5	45
18	M 6	M 8	16	20	25	32	40	50	63	13,5	31	6,5	45	4	62
22	M 10	-	20	25	32	40	50	63	80	16	36	8	52	4	74
25	M 12	-	25	32	40	50	63	80	-	19	43	11	63	4	89
30	M 16	-	32	40	50	63	80	-	-	23	50,5	12	76	5	108

Specification

- Handle
Zinc die casting
- Powder coated
Black, RAL 9005, textured finish ● **SW**
Orange, RAL 2004, textured finish ● **OS**
- Threaded stud and retaining screw
Stainless steel AISI 303
- *Stainless Steel Characteristics* → Page 2166
- **RoHS**

On request

- With inch threads



Information

Adjustable hand levers GN 101.1 are ideal whenever parts have to be clamped in a confined space or in a particular lever position. The centre insert is connected to the lever via serrations which can easily be disengaged.

Pulling the lever disengages serrations and allowing to be swivelled to the ideal clamping position. On releasing the lever the serrations automatically re-engage.

see also...

- *Adjustable Hand Levers GN 101 (Threaded Stud Steel)* → Page 453
- *Adjustable Hand Levers GN 300.1 (Threaded Stud Stainless Steel)* → Page 439
- *Adjustable Hand Levers GN 300.2 (Threaded Stud, Zinc Plated)* → Page 431
- *Flat Adjustable Hand Levers GN 302.1 (Threaded Stud Stainless Steel)* → Page 451
- *Adjustable Stainless Steel Hand Levers GN 300.5* → Page 441
- *Adjustable Hand Levers GN 604.1 (Handle Plastic)* → Page 463

How to order

GN 101.1-22-M10-40-SW

1	d ₁
2	d ₂
3	l ₁
4	Color

