



材質	處理
鋼	鍍鋅、鍍鉻

品號	A	B	C	D ~	E ~	行程 F ~	適用 螺栓	靜荷重 max. kN	動荷重 max. kN	質量 g	庫存			
25120.0006	6.6	25	M15×1	15	19	4	M6	40	30.7	42	△			
25120.0012							M8					55.7	95	△
25120.0014	9.0	32	M20×1	18	23	5	M8	65	48.0	86	△			
25120.0016							M10					37.9	79	△
25120.0022	11.0	45	M30×1.5	22	29	7	M10	120	92.9	210	△			
25120.0024	13.5						M12					80.4	202	△
25120.0026	17.5						M16					45.5	219	△
25120.0032	22.0						M20					136.0	450	△
25120.0034	22.0	58	M40×1.5	28	37	9	M20	210	90.0	392	△			
25120.0036	26.0						M24					37.0	364	△
25120.0042	22.0	70	M50×1.5	33	43	10	M20	330	210.0	773	△			
25120.0044	26.0						M24					157.0	748	△
25120.0046	33.0						M30					53.0	640	△

### SP. 特長

- 適用於機械或工件的高度和水平調整
- 貫穿式中心孔適合鎖固件通過
- 限制最大行程的設計

訂貨：  交期：  天

25120.0006

### Ex. 使用例

