



4 Type

- A Without rubber underlay
- B With rubber underlay

View of magnetic surfaces



3

d ₁	d ₂	h ₁	h ₂	Nominal magnetic force in N	
				Type A	Type B
12	9	16	4,5	55	16

Specification

1

2

- Magnet material
NdFeB **ND**
Neodymium, iron, boron
Temperature resistant up to 80 °C
- Housing
Steel **ST**
Nickel-plated
- Rubber underlay (type B)
Elastomer (TPE)
Black
≈ 80 Shore A
- *Elastomer Characteristics* → Page QVX
- RoHS

Information

Magnets GN 53.4 work in combination with the ergonomic nickel-plated steel handle as a system for holding documents, templates, drawings etc. that are used in technical environments.

The neodymium magnet keeps the required contact diameter small while also supplying a high retaining force.

Type B also features a rubber underlay to protect sensitive surfaces from damage and ensure low noise on contact.

see also...

- *More Information on Retaining Magnets* → Page QVX
- *Magnets GN 53.3 (Disk-Shaped, with Handle)* → Page QVX
- *Magnets GN 53.1 (Disk-Shaped)* → Page QVX
- *Magnets GN 53.2 (Rectangular-Shape)* → Page QVX
- *Magnets GN 51.7 (with Ball Knob / with Key Ring)* → Page QVX

Accessory

- Holding Disks GN 70 → Page QVX
- Adhesive Disks GN 70.1 → Page QVX

How to order

GN 53.4-ND-ST-12-B

- 1 Magnet material
- 2 Material
- 3 d₁
- 4 Type

