



D mm	真圓度 μm
<13	0.004
<20	0.005
<30	0.006

TYPE	公差	材質	熱處理	硬度	表面處理	備註
GKS029-A	g6	SUJ2	高週波	HRC58	-	適用於配合線性襯套 (請參閱線性襯套· 小型滾珠導件單元)
GKS029-B		SUS440C		HRC56		
GKS029-C		SUJ2		HRC58		
GKS029-D		SUS440C		HRC56		
CRS.AG	f8	S45C	-	-	硬鉻	適用於配合自潤軸承
SUSC.AG	f8	SUS304	-	-	-	(請參閱自潤軸承單元)

D mm	淬火深度 (mm)	
	SUJ2	SUS440C
<10	0.5	0.5
<13	0.7	0.5
<20	0.7	0.7
<25	1.0	0.7

L mm	公差 mm
<6	±0.1
<30	±0.2
<120	±0.3
<400	±0.5
<1000	±0.8
<1500	±1.2

品號 TYPE	D	g6公差 mm	f8公差 mm	L 指定單位1mm	L1 指定單位1mm	M	C
(g6) GKS029-A GKS029-B GKS029-C GKS029-D	6	-0.004 -0.012	-0.010 -0.028	25~200	5~7	3	0.5
	8	-0.005 -0.014	-0.013 -0.035	25~200	5~10	3 4 5	0.5
	10	-0.005 -0.014	-0.013 -0.035	30~200	5~14	3 4 5 6	0.5
	12	-0.006 -0.017	-0.016 -0.043	40~300	5~18	4 5 6 8	0.5
(f8) CRS.AG SUSC.AG	13	-0.006 -0.017	-0.016 -0.043	40~300	5~20	4 5 6 8	0.5
	15	-0.006 -0.017	-0.016 -0.043	50~300	10~24	4 5 6 8	0.5
	16	-0.006 -0.017	-0.016 -0.043	50~500	10~25	4 5 6 8 10	0.5
	18	-0.006 -0.017	-0.016 -0.043	60~500	10~28	4 5 6 8 10 12	0.5
20	-0.007 -0.020	-0.020 -0.053	60~500	10~32	4 5 6 8 10 12	1.0	

PS. 備註

· CRS.AG和SUSC.AG的外徑公差是f8，未熱處理

訂貨： TYPE [] D [] L [] L1 [] M [] 交期： 8 天

GKS029-A 12-260-12-8

追加加工

Alteration	變更L尺寸公差	扳手槽追加加工																														
Code	A	B																														
Spec.	<p>變更L尺寸公差 指定方法：A 使用A時， L尺寸可指定單位為0.1mm · L < 200 → L ± 0.03 200 ≤ L < 500 → L ± 0.05 L = 500 → L ± 0.1 · 不適用於D=P · 不適用於一端軸頸內螺牙， 一端外螺牙</p>	<p>做扳手槽追加加工 指定方法：B5 · B=指定單位為1mm · B+1 ≤ L-J B ≥ 0</p> <table border="1"> <thead> <tr> <th>D</th> <th>W</th> <th>11</th> </tr> </thead> <tbody> <tr><td>6</td><td>5</td><td>8</td></tr> <tr><td>8</td><td>7</td><td>8</td></tr> <tr><td>10</td><td>8</td><td>8</td></tr> <tr><td>12</td><td>10</td><td>10</td></tr> <tr><td>13</td><td>11</td><td>10</td></tr> <tr><td>15</td><td>13</td><td>10</td></tr> <tr><td>16</td><td>14</td><td>10</td></tr> <tr><td>18</td><td>16</td><td>10</td></tr> <tr><td>20</td><td>17</td><td>10</td></tr> </tbody> </table>	D	W	11	6	5	8	8	7	8	10	8	8	12	10	10	13	11	10	15	13	10	16	14	10	18	16	10	20	17	10
D	W	11																														
6	5	8																														
8	7	8																														
10	8	8																														
12	10	10																														
13	11	10																														
15	13	10																														
16	14	10																														
18	16	10																														
20	17	10																														

追加加工訂貨： TYPE [] D [] L [] L1 [] M [] A []

GKS029-A 12-260-12-8-A

交期： 8 天

· 追加加工可能會導致硬度降低