



D mm	真圓度 μm
<13	0.004
<20	0.005
<30	0.006

TYPE	公差	材質	熱處理	硬度	表面處理	備註
GKS030-A	g6	SUJ2	高週波	HRC58	-	適用於配合線性襯套 (請參閱線性襯套· 小型滾珠導件單元)
GKS030-B		SUS440C		HRC56		
GKS030-C		SUJ2		HRC58		
GKS030-D		SUS440C		HRC56		
CRS.AH	f8	S45C	-	-	硬鉻	適用於配合自潤軸承 (請參閱自潤軸承單元)
SUSC.AH		SUS304	-	-		

D mm	淬火深度 (mm)	
	SUJ2	SUS440C
<10	0.5	0.5
<13	0.7	0.5
<20	0.7	0.7
<25	1.0	0.7

L mm	公差 mm
<6	±0.1
<30	±0.2
<120	±0.3
<400	±0.5
<1000	±0.8
<1500	±1.2

品號	g6公差 mm	f8公差 mm	L 指定單位1mm		L2 指定單位1mm	L3 指定單位1mm	L4 指定單位1mm	M=P	L1 MAX.	C	
			MIN.	MAX.							
(g6)	6	-0.004	-0.010	25	L2 MIN.=0	當P≤6 L3 MIN.=2	5~7	3 4 5 6	200	0.5	
		-0.012	-0.028								
	8	-0.005	-0.013								
		-0.014	-0.035								
GKS030-A	10	-0.005	-0.013	30	L2 MAX.=L3-2	當P=8 & 10 L3 MIN.=3	5~14	4 5 6 8 10	200	0.5	
		-0.014	-0.035								
GKS030-B	12	-0.006	-0.016								
		-0.017	-0.043								
GKS030-C	13	-0.006	-0.016	40	L1 MAX.=L3	當P=8 & 10 L2 MAX.=L3-3	5~20	5 6 8 10 12	300	0.5	
		-0.017	-0.043								
GKS030-D	15	-0.006	-0.016								
		-0.017	-0.043								
(f8)	CRS.AH	16	-0.006	-0.016	50	當P≥12 L2 MAX.=L3-5	當P≥12 L3 MIN.=5	10~24	5 6 8 10 12	300	0.5
			-0.017	-0.043							
	SUSC.AH	18	-0.006	-0.016							
			-0.017	-0.043							
20	-0.007	-0.020	60	L3 MAX.=P×5	10~28	5 6 8 10 12 16	500	0.5			
	-0.020	-0.053									
20	10~32	5 6 8 10 12 16 20	500	1.0							

PS. 備註

· CRS.AH和SUSC.AH的外徑公差是f8，未熱處理

訂貨： TYPE [] D [] L [] L2 [] L3 [] L4 [] M [] 交期： 8 天

GKS030-A 12 - 280 - 25 - 32 - 10 - 8

追加工

Alteration	扳手槽追加工																															
	M側																															
Code	B																															
Spec.	<p>做扳手槽追加工 指定方法：B5 · B=指定單位為1mm · B+l1≤L-J B≥0</p> <table border="1"> <thead> <tr> <th>D</th> <th>W</th> <th>l1</th> </tr> </thead> <tbody> <tr><td>6</td><td>5</td><td>8</td></tr> <tr><td>8</td><td>7</td><td>8</td></tr> <tr><td>10</td><td>8</td><td>8</td></tr> <tr><td>12</td><td>10</td><td>10</td></tr> <tr><td>13</td><td>11</td><td>10</td></tr> <tr><td>15</td><td>13</td><td>10</td></tr> <tr><td>16</td><td>14</td><td>10</td></tr> <tr><td>18</td><td>16</td><td>10</td></tr> <tr><td>20</td><td>17</td><td>10</td></tr> </tbody> </table>		D	W	l1	6	5	8	8	7	8	10	8	8	12	10	10	13	11	10	15	13	10	16	14	10	18	16	10	20	17	10
D	W	l1																														
6	5	8																														
8	7	8																														
10	8	8																														
12	10	10																														
13	11	10																														
15	13	10																														
16	14	10																														
18	16	10																														
20	17	10																														

追加工訂貨： TYPE [] D [] L [] L2 [] L3 [] L4 [] M [] B []

GKS030-A 12 - 280 - 25 - 32 - 10 - 8 - B5

交期： 8 天

· 追加工可能會導致硬度降低