



D mm	真圓度 μm
<13	0.004
<20	0.005
<30	0.006

TYPE	公差	材質	熱處理	硬度	表面處理	備註
GKS031-A	g6	SUJ2	高週波	HRC58	- 硬鉻	適用於配合線性襯套 (請參閱線性襯套 · 小型滾珠導件單元)
GKS031-B		SUS440C		HRC56		
GKS031-C		SUJ2		HRC58		
GKS031-D		SUS440C		HRC56		
CRS.AK	f8	S45C	-	-	硬鉻	適用於配合自潤軸承 (請參閱自潤軸承單元)
SUSC.AK	f8	SUS304	-	-	-	

D mm	淬火深度 (mm)	
	SUJ2	SUS440C
<10	0.5	0.5
<13	0.7	0.5
<20	0.7	0.7
<25	1.0	0.7

L mm	公差 mm
<6	±0.1
<30	±0.2
<120	±0.3
<400	±0.5
<1000	±0.8
<1500	±1.2

品號		g6公差	f8公差	D1	L	L2	L3	M	L1	C									
TYPE	D	mm	mm	指定單位1mm	指定單位1mm	指定單位1mm	指定單位1mm		MAX.										
(g6)	8	-0.005	-0.013	6	25~198	2 ≤ L2 ≤ D1 × 4	5~10	3	200	0.5									
		-0.014	-0.035																
		-0.005	-0.013																
		-0.014	-0.035																
GKS031-A	10	-0.005	-0.013	6~8	30~198	2 ≤ L2 ≤ D1 × 4	5~14	3 4 5	200	0.5									
-0.014		-0.035																	
GKS031-B		12	-0.006								-0.016	6~10	40~298	2 ≤ L2 ≤ D1 × 4	5~18	3 4 5 6	300	0.5	
GKS031-C			-0.017								-0.043								
GKS031-D	13	-0.006	-0.016	6~11	40~298	2 ≤ L2 ≤ D1 × 4	5~20	3 4 5 6 8	300	0.5									
GKS031-D		-0.017	-0.043																
(f8)	15	-0.006	-0.016	6~13	50~298	2 ≤ L2 ≤ D1 × 4	10~24	3 4 5 6 8 10	300	0.5									
		-0.017	-0.043																
		CRS.AK	16								-0.006	-0.016	6~14	50~498	2 ≤ L2 ≤ D1 × 4	10~25	3 4 5 6 8 10	500	0.5
		SUSC.AK									-0.017	-0.043							
CRS.AK	18	-0.006	-0.016	8~16	60~498	2 ≤ L2 ≤ D1 × 4	10~28	4 5 6 8 10 12	500	0.5									
SUSC.AK		-0.017	-0.043																
SUSC.AK	20	-0.007	-0.020	8~17	60~498	2 ≤ L2 ≤ D1 × 4	10~32	4 5 6 8 10 12	500	1.0									
		-0.020	-0.053																

PS. 備註

· CRS.AK和SUSC.AK的外徑公差是f8，未熱處理

訂貨： TYPE [ ] D [ ] - D1 [ ] - L [ ] - L2 [ ] - L3 [ ] - M [ ] 交期： [ 8 ] 天  
GKS031-A 12 - 10 - 280 - 30 - 12 - 6

追加工

Alteration	扳手槽追加工																														
M側																															
Code	B																														
Spec.	<p>做扳手槽追加工 指定方法：B5 · B=指定單位為1mm · B+l1 ≤ L-J B ≥ 0</p> <table border="1"> <thead> <tr> <th>D</th> <th>W</th> <th>l1</th> </tr> </thead> <tbody> <tr><td>6</td><td>5</td><td>8</td></tr> <tr><td>8</td><td>7</td><td>8</td></tr> <tr><td>10</td><td>8</td><td>8</td></tr> <tr><td>12</td><td>10</td><td>10</td></tr> <tr><td>13</td><td>11</td><td>10</td></tr> <tr><td>15</td><td>13</td><td>10</td></tr> <tr><td>16</td><td>14</td><td>10</td></tr> <tr><td>18</td><td>16</td><td>10</td></tr> <tr><td>20</td><td>17</td><td>10</td></tr> </tbody> </table>	D	W	l1	6	5	8	8	7	8	10	8	8	12	10	10	13	11	10	15	13	10	16	14	10	18	16	10	20	17	10
D	W	l1																													
6	5	8																													
8	7	8																													
10	8	8																													
12	10	10																													
13	11	10																													
15	13	10																													
16	14	10																													
18	16	10																													
20	17	10																													

追加工訂貨： TYPE [ ] D [ ] - D1 [ ] - L [ ] - L2 [ ] - L3 [ ] - M [ ] - B [ ]  
GKS031-A 12 - 10 - 280 - 30 - 12 - 6 - B5

交期： [ 8 ] 天

· 追加工可能會導致硬度降低