



2

d ₁	d ₂	d ₃	l ₁ ≈	l ₂	l ₃	l ₄ ≈	l ₅
16	M 5	16	58	15	5	52,5	9,5
18	M 5	16	72,5	15	5	67	9,5
22	M 6	20	80,5	19,5	6	74	10,5
24	M 6	20	95,5	19,5	6	89	10,5
25	M 6	20	105,5	19,5	6	98,5	10,5

Specification

- Handle
Plastic
Technopolymer (Polyamide PA)
- Temperature resistant up to 90 °C
- Black, matte finish
- Revolving

KT

- **GN 798.3**
Retractable mechanism
Steel
Blackened

- **GN 798.5**
Retractable mechanism
Stainless steel
- Spindle
AISI 303
- Flat base
Sintered steel AISI 316LHC

- *Plastic Characteristics* → Page 2158
- *Stainless Steel Characteristics* → Page 2166
- RoHS

Information

Typical in design are the retractable handles GN 798.3 / GN 798.5 with their stepped shape consisting of two cylinders giving the operator a better grip, especially when pulling the handle out from its locked position before it can be folded back into the rest position.

Retractable handles GN 798.3 / GN 798.5 are used when the handle should not protrude temporarily for space or safety reasons.

see also...

- *Retractable Handles GN 598.3 (with Hold in Both Positions, Steel)* → Page 54
- *Retractable Handles GN 598.5 (with Hold in Both Positions, Stainless Steel)* → Page 54

How to order (Retractable mechanism steel)	1	Material
	2	d ₁
GN 798.3-KT-22		

How to order (Retractable mechanism SST)	1	Material
	2	d ₁
GN 798.5-KT-25		