



d ₁	d ₂		Material				d ₃	d ₄	l ₁	l ₂	l ₃
	Plastic	KT	KT	KT	Steel	ST					
14	-	-	M 6	-	-	-	8	11	28	10	0,5
18	M 6	-	M 6	-	M 6	-	10	15	40	12	2,5
21	M 6	M 8	M 6	M 8	M 6	M 8	10	17	50	13	2,5
22	M 6	M 8	M 6	M 8	-	-	10	18	56	13	2,5
23	M 8	M 10	M 8	M 10	M 8	M 10	13	19	65	14	2,5
26	M 8	M 10	M 8	M 10	M 8	M 10	13	21	80	16	2,5
28	M 10	-	M 10	-	M 10	-	13	22	90	16	2,5
31	M 12	-	-	-	M 12	-	14	25	102	20	2,5

Specification

- Plastic
Duroplast (Phenolic PF)
- Temperature resistant up to 110 °C
- Black, shiny finish
- Plastic
Technopolymer (Polypropylene PP)
- Temperature resistant up to 80 °C
- Black, matte finish
- Black, shiny finish (only size 14)
- Steel
Powder coated
Black, textured finish
- Spindle
Steel
Zinc plated, blue passivated
- *Plastic Characteristics* → Page 2158
- RoHS

On request

- With inch threads



Information

KU

Steel revolving handles GN 598 are mainly used on safety handwheels to increase imbalance and thus avoid free wheeling.

see also...

- *Fixed Cylindrical Handles GN 539* → Page 48
- *Retractable Handles GN 598.3 (with Hold in Both Positions)* → Page 54

KT

ST

How to order

GN598-KU-21-M8

1 Material

2 d₁

3 d₂