



**3 Type**

- D With plain shaft
- E With threaded shaft

**2**

d <sub>1</sub>	d <sub>2</sub> h8 Type D	d <sub>3</sub> Type E			d <sub>4</sub> h13	l <sub>1</sub> ≈	l <sub>2</sub>	l <sub>3</sub>	A/F Internal hexagon ST / KT
	ST	ST	A4	KT					
16	7	M 6	M 6	-	10	50	11	7	3
20	8	M 8	M 8	M 8	13	64	13	8	4
25	10	M 10	M 10	M 10	16	80	14	10	5
32	13	M 12	-	M 12	20	100	21	13	6
36	16	M 16	-	-	22	112	26	14	8

**Specification**

- Steel **ST**
- Zinc plated, blue passivated
- Stainless steel AISI 316L **A4**
- Plastic **KT**
- Technopolymer (Polyamide PA)
- Temperature resistant up to 100 °C
- Black, matte finish
- Threaded stud
- Steel, blackened
- ISO Fundamental Tolerances → Page 2151
- Plastic Characteristics → Page 2158
- Stainless Steel Characteristics → Page 2166
- RoHS

**1**

**Information**

On the official DIN standard sheet you can find the additional sizes 10 and 13.  
For reasons of hygiene, no internal hexagon is used in type A4.

**How to order**

**DIN 39-ST-25-E**

- 1 Material
- 2 d<sub>1</sub>
- 3 Type

1.1  
1.2  
1.3  
1.4  
2.1  
2.2  
2.3  
2.4

