



**3 Type**

**A** Mounting from the back (threaded blind bore)

1					2		4					
d <sub>1</sub>	Length l ±0,25					d <sub>2</sub>	b <sub>1</sub>	b <sub>2</sub>	h <sub>1</sub>	h <sub>2</sub>	t min.	
28	242	292	392	492	592	M 8	25	14	50	66	15	

**Specification**

- Handle tube  
Aluminum (wall thickness 1,5)
- Handle legs  
Zinc die casting  
Powder coated
- Tube / handle legs **● SW**  
Powder coated  
Black, RAL 9005, textured finish  
Cover  
Plastic, black, matte finish
- Tube **● ELS**  
Anodized, natural color  
Handle legs  
Black, RAL 9005, textured finish  
Cover  
Plastic, black, matte finish
- Tube **● ELG**  
Anodized, natural color  
Handle legs  
Silver, RAL 9006, textured finish  
Cover  
Plastic, light gray, matte finish
- *Load Rating Information* → Page 2106
- **RoHS**

**Accessory**

- Handle Legs GN 333.9 → Page 183

**On request**

- Special lengths

**Information**

The spacing of the attachment holes of the tubular handles GN 333.3 is adjustable.

Further handle legs can be added for very long tubular handles. Individual handle legs for tubular handles Ø 28 (type A) are available under GN 333.9.

Tubular handles GN 333.3 are supplied unassembled.

see also...

- *Handle Tubes GN 930* → Page 209

How to order		1	d <sub>1</sub>
		2	Length l
		3	Type
		4	Finish
<b>GN 333.3-28-292-A-ELG</b>			