



材質	硬度	螺紋精度	平面偏擺	螺紋精度	平面偏擺
SCM440	HRC28~32	ISO 4H 精密研磨	0.002mm	ISO 6H 精密車削	0.005mm

品號	螺牙	D	h	d	n×g	φb	t	c	M	軸向負載能力 (KN)	扭緊力矩 (max.Nm)	鬆脫力矩	單價													
YSF-0002	M14×1.5	30	14	25	3×4	-	2	-	M5	-	4.5	-	•													
YSF-0004	M15×1									-		-														
YSF-0006	M16×1.5	-	-																							
YSF-0008	M17×1	-	-																							
YSF-0010	M18×1.5	-	-																							
YSF-0012	M20×1	38	16	33					3×5	-	-	M6	80	8	27.5	•										
YSF-0014	M20×1.5												-		-											
YSF-0016	M22×1.5												-		-											
YSF-0018	M24×1.5												-		-											
YSF-0020	M25×1.5												-		-											
YSF-0022	M27×1.5	40	18	35	3×6	2.5	-	M8				-	18	28.9	•											
YSF-0024	M30×1.5											-		-												
YSF-0026	M33×1.5											-		-												
YSF-0028	M35×1.5											-		-												
YSF-0030	M36×1.5	52	20	47								3×7		6	-	M8	90	18	-	•						
YSF-0032									-	-																
YSF-0034	M40×1.5	58	20	52					3×8	3.5	-						M8		18	30.4	•					
YSF-0036	M42×1.5																			-	-					
YSF-0038	M45×1.5																			-	-					
YSF-0040	M48×1.5																			-	-					
YSF-0042	M50×1.5	70	24	64	6×8	7	-	M8					18							-	•					
YSF-0044	M52×1.5																			-	-					
YSF-0046	M55×1.5	75	22	68																6×10	4	110	M8	18	-	•
YSF-0048	M56×2																								-	-
YSF-0050	M60×2	80	24	73								6×10		4	110	M8		18							-	•
YSF-0052	M64×2																								-	-
YSF-0054	M65×2								-	-																
YSF-0056	M68×2								-	-																
YSF-0058	M70×2	92	24	84					6×10	4	110						M8		18						-	•
YSF-0060	M72×2																								-	-
YSF-0062	M75×2	98	24	90	6×10	4	110	M8					18												-	•
YSF-0064	M76×2																								-	-
YSF-0066	M80×2	105	26	96																6×10	4	110	M8	18	-	•
YSF-0068	M85×2																								-	-
YSF-0070	M90×2	120	26	108								6×10		4	110	M8		18							-	•
YSF-0072	M95×2																								-	-

品號	螺牙	D	h	d	n×g	φb	t	c	M	軸向負載能力 (KN)	扭緊力矩 (max.Nm)	鬆脫力矩	單價				
YSF-0074	M100×2	130	26	118	6×10	7	4	115	M 8	740	18	220.6	•				
YSF-0076	M105×2	140	125	123				770	236.3	•							
YSF-0078	M110×2	145	28	128				800	252	•							
YSF-0080	M115×2	150	137	133				830	268.1	•							
YSF-0082	M120×2	155	30	142	6×12	7	5	138	M10	860	35	279.4	•				
YSF-0084	M125×2	160		147				143		890		289.2	•				
YSF-0086	M130×2	165		152				148		920		313.7	•				
YSF-0088	M135×2	175	160	155				950		352.9		•					
YSF-0090	M140×2	180	32	165	6×14	8	6	160		M12		980	60	392.2	•		
YSF-0092	M145×2	190		175				168				1010		436.3	•		
YSF-0094	M150×2	195		180				173				1040		480.4	•		
YSF-0096	M155×3	200	34	185				6×16				7		7	178	M10	1070
YSF-0098	M160×3	210		190	188	1100	563.7								•		
YSF-0100	M165×3	220		200	195	1130	598								•		
YSF-0102	M170×3	230	205	205	1160	647.1	•										
YSF-0104	M180×3	230	36	215	6×16	7	7	215				M12		1220	60		686.3
YSF-0106	M190×3	240		225				215	1280		735.3			•			
YSF-0108	M200×3	250		38				225	1340		794.1			•			

Wa) 注意

- 鎖定方式為螺紋半角30°角,三點式鎖定
- 本產品為本司標準產品,其優異的鎖定設計,能使固定銅上之螺紋,完全契合於公螺紋上,使其防鬆效果完美無缺更因為其30°角的设计,減少了因為鎖緊螺絲因而產生的力矩(此力矩如果超過軸向負荷)
- 1 Nm = 10.2 kgf.cm = 0.73 lb.ft

訂貨: 交期:

YSF - 0002