



材質	硬度	螺紋精度	平面偏擺	螺紋精度	平面偏擺
SCM440	HRC28~32	ISO 4H 精密研磨	0.002mm	ISO 6H 精密車削	0.005mm

品號	螺牙	D	h	g	t	d	n-M	軸向負載能力 (KN)	扭緊力矩 (max.Nm)	鬆脫力矩	單價
YSA-0002	M14×1.5	30	14	4	2	25	2-M4	-	3.5	-	•
YSA-0004	M15×1							-		-	•
YSA-0006	M16×1.5							-		-	•
YSA-0008	M17×1							-		-	•
YSA-0010	M18×1.5	32	16	5	2	27	3-M4	80	-	24.5	•
YSA-0012	M20×1							-	-	•	
YSA-0014	M20×1.5							-	-	•	
YSA-0016	M22×1.5							-	-	•	
YSA-0018	M24×1.5	38	18	5	2	33	3-M4	-	-	-	•
YSA-0020	M25×1.5							-	-	•	
YSA-0022	M27×1.5							-	-	•	
YSA-0024	M30×1.5							-	-	•	
YSA-0026	M33×1.5	50	20	6	2.5	40	3-M6	160	-	29.4	•
YSA-0028	M35×1.5							-	-	•	
YSA-0030	M36×1.5							-	-	•	
YSA-0032	M39×1.5							-	-	•	
YSA-0034	M40×1.5	58	22	7	3	52	3-M6	210	-	42.2	•
YSA-0036	M42×1.5							-	-	•	
YSA-0038	M45×1.5							-	-	•	
YSA-0040	M48×1.5							-	-	•	
YSA-0042	M50×1.5	70	24	8	3.5	64	3-M8	240	-	58.8	•
YSA-0044	M52×1.5							-	-	•	
YSA-0046	M55×2							-	-	•	
YSA-0048	M56×2							-	-	•	
YSA-0050	M60×2	80	26	10	4	73	3-M8	380	-	81.4	•
YSA-0052	M64×2							-	-	•	
YSA-0054	M65×2							-	-	•	
YSA-0056	M68×2							-	-	•	
YSA-0058	M70×2	92	28	12	5	84	3-M8	460	-	88.2	•
YSA-0060	M72×2							-	-	•	
YSA-0062	M75×2							-	-	•	
YSA-0064	M76×2							-	-	•	
YSA-0066	M80×2	105	30	14	6	96	3-M8	520	-	102.9	•
YSA-0068	M85×2							-	-	•	
YSA-0070	M90×2							-	-	•	
YSA-0072	M95×2							-	-	•	

品號	螺牙	D	h	g	t	d	n-M	軸向負載能力 (KN)	扭緊力矩 (max.Nm)	鬆脫力矩	單價	
YSA-0074	M100×2	130	26	10	4	118	3-M8	740	18	171.6	•	
YSA-0076	M105×2	140	28	12	5	125		770	186.3	•		
YSA-0078	M110×2	145				132		800	205.9	•		
YSA-0080	M115×2	150	30			137		830	220.6	•		
YSA-0082	M120×2	155				142		860	235.3	•		
YSA-0084	M125×2	160				147		890	250	•		
YSA-0086	M130×2	165				152		920	264.7	•		
YSA-0088	M135×2	175				-		-	-	160	950	303.9
YSA-0090	M140×2	180				32	14	6	165	980	323.5	•
YSA-0092	M145×2	190	175	1010	352.9				•			
YSA-0094	M150×2	195	34	16	7				180	1040	392.2	•
YSA-0096	M155×3	200							1070	421.6	•	
YSA-0098	M160×3	210							1100	460.8	•	
YSA-0100	M165×3								1130	495.1	•	
YSA-0102	M170×3	220							1160	519.6	•	
YSA-0104	M180×3	230							36	18	8	205
YSA-0106	M190×3	240	215			1280	598	•				
YSA-0108	M200×3	250	38			225	1340	637.3				•

Wa) 注意

- 鎖定方式軸向三點式鎖定,其厚度與YSF系列相同,軸向三點式鎖定為其特點,適用於裝配工作的特殊環境限制

· 1 Nm = 10.2 kgf.cm = 0.73 lb.ft

訂貨： 交期：

YSA-0002