



| 材質     | 硬度       | 螺紋精度           | 平面偏擺    | 螺紋精度           | 平面偏擺    |
|--------|----------|----------------|---------|----------------|---------|
| SCM440 | HRC28~32 | ISO 4H<br>精密研磨 | 0.002mm | ISO 6H<br>精密車削 | 0.005mm |

| 品號       | 螺牙       | D  | h  | g | t   | d  | n-M  | 軸向負載能力 (KN) | 扭緊力矩 (max.Nm) | 鬆脫力矩  | 單價 |
|----------|----------|----|----|---|-----|----|------|-------------|---------------|-------|----|
| YSR-0002 | M 6×0.5  | 16 | 8  | 3 | 2   | 11 | 2-M4 | -           | 3.5           | -     | •  |
| YSR-0004 | M 8×0.75 |    |    |   |     | 13 |      | 30          |               | 17.6  | •  |
| YSR-0006 | M10×0.75 | 18 | 8  | 3 | 2   | 13 | 2-M4 | 35          | 3.5           | 18.1  | •  |
| YSR-0008 | M10×1    |    |    |   |     | 16 |      | 40          |               | 19.1  | •  |
| YSR-0010 | M12×1    | 20 | 8  | 3 | 2   | 16 | 2-M4 | -           | 3.5           | -     | •  |
| YSR-0012 | M12×1.25 |    |    |   |     | 21 |      | 60          |               | 20.6  | •  |
| YSR-0014 | M14×1.5  | 25 | 8  | 3 | 2   | 21 | 2-M4 | -           | 3.5           | -     | •  |
| YSR-0016 | M15×1    |    |    |   |     | 23 |      | 80          |               | 21.6  | •  |
| YSR-0018 | M16×1.5  | 28 | 10 | 4 | 2   | 23 | 2-M5 | -           | 4.5           | -     | •  |
| YSR-0020 | M17×1    |    |    |   |     | 25 |      | 90          |               | 24    | •  |
| YSR-0022 | M18×1.5  | 30 | 10 | 4 | 2   | 25 | 2-M5 | -           | 4.5           | -     | •  |
| YSR-0024 | M20×1    |    |    |   |     | 27 |      | 90          |               | 24    | •  |
| YSR-0026 | M20×1.5  | 32 | 10 | 4 | 2   | 27 | 3-M5 | 90          | 4.5           | 24    | •  |
| YSR-0028 | M22×1.5  |    |    |   |     | 30 |      | -           |               | -     | •  |
| YSR-0030 | M24×1.5  | 38 | 12 | 5 | 2   | 33 | 3-M5 | 130         | 8             | 26.5  | •  |
| YSR-0032 | M25×1.5  |    |    |   |     | 37 |      | -           |               | -     | •  |
| YSR-0034 | M27×1.5  | 42 | 12 | 5 | 2   | 37 | 3-M5 | -           | 8             | -     | •  |
| YSR-0036 | M30×1.5  |    |    |   |     | 40 |      | 160         |               | 28.4  | •  |
| YSR-0038 | M33×1.5  | 52 | 12 | 5 | 2   | 45 | 3-M5 | -           | 8             | -     | •  |
| YSR-0040 | M35×1.5  |    |    |   |     | 47 |      | 190         |               | 34.3  | •  |
| YSR-0042 | M36×1.5  | 55 | 14 | 6 | 2.5 | 49 | 3-M6 | -           | 8             | -     | •  |
| YSR-0044 | M39×1.5  |    |    |   |     | 52 |      | 210         |               | 36.3  | •  |
| YSR-0046 | M40×1.5  | 58 | 14 | 6 | 2.5 | 52 | 3-M6 | 240         | 18            | 56.9  | •  |
| YSR-0048 | M42×1.5  |    |    |   |     | 56 |      | -           |               | -     | •  |
| YSR-0050 | M45×1.5  | 65 | 14 | 6 | 2.5 | 59 | 3-M6 | 240         | 18            | 56.9  | •  |
| YSR-0052 | M48×1.5  |    |    |   |     | 62 |      | -           |               | -     | •  |
| YSR-0054 | M50×1.5  | 70 | 16 | 7 | 3   | 64 | 3-M8 | 300         | 18            | 63.7  | •  |
| YSR-0056 | M52×1.5  |    |    |   |     | 66 |      | -           |               | -     | •  |
| YSR-0058 | M55×2    | 75 | 16 | 7 | 3   | 68 | 3-M8 | 340         | 18            | 68.6  | •  |
| YSR-0060 | M56×2    |    |    |   |     | 70 |      | -           |               | -     | •  |
| YSR-0062 | M60×2    | 80 | 16 | 7 | 3   | 73 | 3-M8 | 380         | 18            | 96.1  | •  |
| YSR-0064 | M64×2    |    |    |   |     | 78 |      | -           |               | -     | •  |
| YSR-0066 | M65×2    | 85 | 16 | 7 | 3   | 78 | 3-M8 | 460         | 18            | 112.7 | •  |
| YSR-0068 | M68×2    |    |    |   |     | 84 |      | -           |               | -     | •  |
| YSR-0070 | M70×2    | 92 | 18 | 8 | 3.5 | 84 | 3-M8 | 490         | 18            | 137.3 | •  |
| YSR-0072 | M72×2    |    |    |   |     | 86 |      | -           |               | -     | •  |

| 品號       | 螺牙     | D   | h    | g     | t     | d    | n-M   | 軸向負載能力<br>(KN) | 扭緊力矩<br>(max.Nm) | 鬆脫力矩  | 單價 |       |       |   |
|----------|--------|-----|------|-------|-------|------|-------|----------------|------------------|-------|----|-------|-------|---|
| YSR-0074 | M 75×2 | 98  | 18   | 8     | 3.5   | 90   | 3-M8  | 520            | 18               | 145.1 | •  |       |       |   |
| YSR-0076 | M 76×2 | 100 |      |       |       | 92   |       | -              |                  | -     |    |       |       |   |
| YSR-0078 | M 80×2 | 105 |      |       |       | 96   |       | 620            |                  | 149   | •  |       |       |   |
| YSR-0080 | M 85×2 | 110 |      |       |       | 102  |       | 650            |                  | 168.6 | •  |       |       |   |
| YSR-0082 | M 90×2 | 120 | 20   | 10    | 4     | 108  |       | 680            |                  | 178.4 | •  |       |       |   |
| YSR-0084 | M 95×2 | 125 |      |       |       | 113  |       | 710            |                  | 193.1 | •  |       |       |   |
| YSR-0086 | M100×2 | 130 |      |       |       | 118  |       | 740            |                  | 210.8 | •  |       |       |   |
| YSR-0088 | M105×2 | 140 |      |       |       | 125  |       | 770            |                  | 215.7 | •  |       |       |   |
| YSR-0090 | M110×2 | 145 | 22   | 12    | 5     | 132  |       | 800            |                  | 230.4 | •  |       |       |   |
| YSR-0092 | M115×2 | 150 |      |       |       | 137  |       | 830            |                  | 250   | •  |       |       |   |
| YSR-0094 | M120×2 | 155 | 24   |       |       | 142  |       | 860            |                  | 264.7 | •  |       |       |   |
| YSR-0096 | M125×2 | 160 |      |       |       | 147  |       | 890            |                  | 274.5 | •  |       |       |   |
| YSR-0098 | M130×2 | 165 |      |       |       | 152  | 920   | 294.1          | •                |       |    |       |       |   |
| YSR-0100 | M135×2 | 175 |      |       |       | 26   | 14    | 6              | 160              | 3-M10 | 35 | 328.4 | •     |   |
| YSR-0102 | M140×2 | 180 | 165  | 980   | 372.5 |      |       |                | •                |       |    |       |       |   |
| YSR-0104 | M145×2 | 190 | 175  | 1010  | 402   |      |       |                | •                |       |    |       |       |   |
| YSR-0106 | M150×2 | 195 | 180  | 1040  | 421.6 |      |       |                | •                |       |    |       |       |   |
| YSR-0108 | M155×3 | 200 | 1070 | 460.8 | •     |      |       |                |                  |       |    |       |       |   |
| YSR-0110 | M160×3 | 210 | 28   | 16    | 7     |      |       |                | 190              |       |    | 1100  | 509.8 | • |
| YSR-0112 | M165×3 |     |      |       |       | 1130 | 529.4 | •              |                  |       |    |       |       |   |
| YSR-0114 | M170×3 | 220 |      |       |       | 200  | 1160  | 558.8          | •                |       |    |       |       |   |
| YSR-0116 | M180×3 | 230 |      |       |       | 30   | 18    | 8              | 205              | 3-M12 | 60 | 558.2 | •     |   |
| YSR-0118 | M190×3 | 240 |      |       |       |      |       |                | 215              |       |    | 1280  | 627.5 | • |
| YSR-0120 | M200×3 | 250 |      |       |       |      |       |                | 225              |       |    | 1340  | 666.7 | • |

**Wa. 注意**

· 鎖定方式為徑向三點式鎖定,其厚度相較其它產品為薄,適用於螺帽厚度空間受到限制,無法使用其他產品之情況

· 1 Nm = 10.2 kgf.cm = 0.73 lb.ft

訂貨：  交期：

YSR-0002