



EDDELSTAHL®  
Rost  
frei  
Inox  
Stainless  
Steel

**4 Type (Base plate)**

**B1** Matte shot-blasted,  
rubber inlaid, black

<b>d<sub>1</sub></b>	<b>d<sub>2</sub></b>	<b>l<sub>1</sub></b>		<b>Version T / TK und U / UK</b>								<b>l<sub>2</sub></b> Version V / VK				<b>l<sub>3</sub></b> Version W				<b>l<sub>7</sub></b> Vers. X	<b>A/F<sub>7</sub></b>	<b>t</b>
50	M 8	40	50	63	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	40	14	8
50	M 10	50	60	80	100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	43	14	10
50	M 12	60	80	100	125	-	-	-	-	-	-	-	-	-	-	-	-	-	-	47	17	12
50	M 16	-	-	-	-	75	100	125	150	200	250	-	-	-	-	-	-	-	-	52	22	16
60	M 8	40	50	63	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	41	14	8
60	M 10	50	60	80	100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	44	14	10
60	M 12	60	80	100	125	-	-	-	-	-	-	-	-	-	-	-	-	-	-	48	17	12
60	M 16	-	-	-	-	75	100	125	150	200	250	75	100	125	150	126	151	176	201	53	22	16
80	M 8	40	50	63	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	42	14	8
80	M 10	50	60	80	100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	45	14	10
80	M 12	60	80	100	125	-	-	-	-	-	-	-	-	-	-	-	-	-	-	49	17	12
80	M 16	-	-	-	-	75	100	125	150	200	250	75	100	125	150	127	152	177	202	54	22	16
80	M 20	-	-	-	-	75	100	125	150	200	250	100	125	150	200	151	176	201	251	62	27	20
80	M 24	-	-	-	-	100	125	150	200	300	-	100	150	200	-	176	226	276	-	-	-	-
100	M 8	40	50	63	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	43	14	8
100	M 10	50	60	80	100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	46	14	10
100	M 12	60	80	100	125	-	-	-	-	-	-	-	-	-	-	-	-	-	-	50	17	12
100	M 16	-	-	-	-	75	100	125	150	200	250	75	100	125	150	128	153	178	203	55	22	16
100	M 20	-	-	-	-	75	100	125	150	200	250	100	125	150	200	152	177	202	252	63	27	20
100	M 24	-	-	-	-	100	125	150	200	300	-	100	150	200	-	177	227	277	-	-	-	-

**Specification**

- Base plate / flange  
Stainless steel AISI 304
- Threaded stem  
Stainless steel AISI 303
- Hexagon nut ISO 4032  
Stainless steel AISI 304
- Rubber pad, inlaid  
Black, NBR (Perbunan®)  
80±5 Shore A
- *Elastomer Characteristics*  
→ Page 2158
- *Stainless Steel Characteristics*  
→ Page 2166
- **RoHS**

**Versions of threaded stem**

<p><b>S</b> Without nut <b>SK</b> With nut</p>	<p><b>T</b> Without nut <b>TK</b> With nut</p>	<p><b>U</b> Without nut <b>UK</b> With nut</p>
<p>External hexagon at the bottom at <math>d_2</math> M 8, M 10, M 12</p>	<p>Wrench flat at the bottom at <math>d_2</math> M 16, M 20, M 24</p>	<p>Hexagon socket at the top and wrench flat at the bottom at <math>d_2</math> M 16, M 20, M 24</p>
<p><b>V</b> Without nut <b>VK</b> With nut</p>	<p><b>W</b> With adjustable sleeve</p>	<p><b>X</b> With internal thread</p>
<p>External hexagon at the top and wrench flat at the bottom at <math>d_2</math> M 16, M 20, M 24</p>	<p>Covered thread and wrench flat at the bottom at <math>d_2</math> M 16, M 20, M 24</p>	<p>External hexagon with internal thread at <math>d_2</math> M 8, M 10, M 12, M 16, M 20</p>

$d_1$	$d_2$	$d_3$	$d_4$	$h_1$	$h_3$	$h_4$	$h_5$	$l_4$	$l_5$	$l_6$	$l_8$	$l_9$	A/F <sub>1</sub>	A/F <sub>2</sub>	A/F <sub>3</sub>	A/F <sub>4</sub>	A/F <sub>5</sub>	A/F <sub>6</sub>
50	M 8 M 10 M 12	- 13	13	18	26	-	-	-	-	-	25	45	17	-	-	-	-	-
50	M 16	-	13	18	-	32	-	-	-	-	25	45	-	12	8	-	-	-
60	M 8 M 10 M 12	- 13	13	19	27	-	-	-	-	-	25	50	17	-	-	-	-	-
60	M 16	-	24 13	19	-	33 30	45 45	29	25	50	-	12	8	10	12	20	-	-
80	M 8 M 10 M 12	- 13	13	20	28	-	-	-	-	-	30	70	17	-	-	-	-	-
80	M 16	-	24 13	20	-	34 31	45 45	29	30	70	-	12	8	10	12	20	-	-
80	M 20	-	30 13	20	-	35 32	56 56	36	30	70	-	15	10	13	16	24	-	-
80	M 24	-	35 13	20	-	38 35	67 67	42	30	70	-	19	12	17	20	30	-	-
100	M 8 M 10 M 12	- 13	13	21	29	-	-	-	-	-	30	80	17	-	-	-	-	-
100	M 16	-	24 13	21	-	35 32	45 45	29	30	80	-	12	8	10	12	20	-	-
100	M 20	-	30 13	21	-	36 33	56 56	36	30	80	-	15	10	13	16	24	-	-
100	M 24	-	35 13	21	-	39 36	67 67	42	30	80	-	19	12	17	20	30	-	-

**Information**

Stainless steel leveling feet GN 33 will be delivered mounted and are not removable.

• [Load Rating Information](#) → Page 2143

see also...

- [Leveling Feet GN 32 \(Steel, Zinc Plated\)](#) → Page 1480
- [SST Leveling Feet GN 31 \(without Flange\)](#) → Page 1478
- [Insert Bushings GN 448 \(for Tubes\)](#) → Page 1498 / 1499

**How to order**

1	$d_1$
2	$d_2$
3	$l_1$ ( $l_2, l_3, l_7$ )
4	Type (Base plate)
5	Version (Stem)

GN33-60-M16-100-B1-V