



| 材質 | 硬度 | 螺紋精度 | 平面偏擺 |
|--------|----------|----------------|---------|
| SCM440 | HRC28~32 | ISO 6H 精密車削 | 0.005mm |

| 品號 | 螺牙 | D | h | d | n-M x L | n | φb | c | 軸向負載能力 (KN) | 扭緊力矩 (max.Nm) | 鬆脫力矩 | 單價 | | | | | | | | | | | | | |
|----------|-----------|-----|-----|----|-----------|-----------|-------|-----|-------------|---------------|------|-------|-------|-------|-----|-----|-------|-----|-------|---|-----|-----|-------|---|-----|
| YSK-0002 | M16 x 1.5 | 34 | 18 | 29 | 4-M4 x 12 | 4 | 4 | 24 | - | 3.5 | - | • | | | | | | | | | | | | | |
| YSK-0004 | M17 x 1 | 37 | | 32 | | | | 26 | 80 | | 90 | • | | | | | | | | | | | | | |
| YSK-0006 | M18 x 1.5 | 38 | | 33 | | | | 28 | - | | - | • | | | | | | | | | | | | | |
| YSK-0008 | M20 x 1 | 40 | | 35 | | | | 30 | 90 | | 99 | • | | | | | | | | | | | | | |
| YSK-0010 | M20 x 1.5 | | | 37 | | | | 32 | - | | - | • | | | | | | | | | | | | | |
| YSK-0012 | M22 x 1.5 | 42 | | 39 | | | | 34 | - | | - | • | | | | | | | | | | | | | |
| YSK-0014 | M24 x 1.5 | 44 | | 20 | | | | 40 | 4-M4 x 14 | | 4 | 35 | 130 | 3.5 | 101 | • | | | | | | | | | |
| YSK-0016 | M25 x 1.5 | 45 | 43 | | - | - | • | | | | | | | | | | | | | | | | | | |
| YSK-0018 | M26 x 1.5 | 46 | | | 39 | 160 | 102 | | | • | | | | | | | | | | | | | | | |
| YSK-0020 | M28 x 1.5 | 48 | 22 | | 47 | 4-M4 x 16 | 5 | 41 | | - | | - | • | | | | | | | | | | | | |
| YSK-0022 | M30 x 1.5 | 48 | | | | | | 44 | | 190 | | 109.8 | • | | | | | | | | | | | | |
| YSK-0024 | M32 x 1.5 | 50 | | | | | | 53 | | - | | - | • | | | | | | | | | | | | |
| YSK-0026 | M35 x 1.5 | 53 | | | | | | 55 | | 210 | | 110.8 | • | | | | | | | | | | | | |
| YSK-0028 | M38 x 1.5 | 56 | | 25 | | | | 63 | 6-M4 x 18 | 6 | 57 | 240 | - | 127.5 | • | | | | | | | | | | |
| YSK-0030 | M40 x 1.5 | 58 | | | | | | | | | 66 | 300 | 137.3 | • | | | | | | | | | | | |
| YSK-0032 | M42 x 1.5 | 60 | | | | | | | | | | | | | 62 | - | - | • | | | | | | | |
| YSK-0034 | M45 x 1.5 | 68 | 26 | | 71 | 6-M5 x 20 | 6 | | | | 65 | 340 | 166.7 | • | | | | | | | | | | | |
| YSK-0036 | M48 x 1.5 | 69 | | | | | | | | | 77 | - | - | • | | | | | | | | | | | |
| YSK-0038 | M50 x 1.5 | 70 | | | | | | | | | | | | | 72 | 380 | 205.9 | • | | | | | | | |
| YSK-0040 | M52 x 1.5 | 72 | | | | | | | | | 75 | - | - | • | | | | | | | | | | | |
| YSK-0042 | M55 x 1.5 | 75 | | 82 | | | | - | - | • | | | | | | | | | | | | | | | |
| YSK-0044 | M55 x 2 | | | | | | | | | | 28 | 84 | 460 | 254.9 | • | | | | | | | | | | |
| YSK-0046 | M58 x 1.5 | 82 | | 80 | | | | - | - | • | | | | | | | | | | | | | | | |
| YSK-0048 | M60 x 1.5 | 84 | 82 | | 490 | 313.7 | • | | | | | | | | | | | | | | | | | | |
| YSK-0050 | M60 x 2 | 100 | | 89 | | | | 520 | 382.4 | • | | | | | | | | | | | | | | | |
| YSK-0052 | M62 x 1.5 | | 86 | | 87 | 520 | 382.4 | | | | | | | | | • | | | | | | | | | |
| YSK-0054 | M65 x 1.5 | | 88 | | | | | | | | | | | | | | 95 | 620 | 460.8 | • | | | | | |
| YSK-0056 | M65 x 2 | | 32 | | 103 | 6-M6 x 22 | 8 | | | | | | | | | 100 | | | | | 650 | 8 | 549 | • | |
| YSK-0058 | M68 x 1.5 | | | | | | | | | | 93 | 91 | - | - | • | | | | | | | | | | |
| YSK-0060 | M70 x 1.5 | | | | | | | | | | 95 | | | | | | 87 | 520 | 382.4 | • | | | | | |
| YSK-0062 | M70 x 2 | | | | | | | | | | 100 | 94 | 520 | 382.4 | • | | | | | | | | | | |
| YSK-0064 | M72 x 1.5 | 97 | | 87 | | | | 520 | 382.4 | • | | | | | | | | | | | | | | | |
| YSK-0066 | M75 x 1.5 | 100 | | | | | | | | | | | | | | | 94 | 520 | 382.4 | • | | | | | |
| YSK-0068 | M75 x 2 | | | 32 | | | | 108 | 6-M6 x 22 | 8 | | | | | | | | | | | | | | | 100 |
| YSK-0070 | M80 x 2 | | 110 | | 95 | 620 | 460.8 | | | | | | | | | • | | | | | | | | | |
| YSK-0072 | M85 x 2 | | 115 | | | | | | | | | | | | | | | | | | 87 | 520 | 382.4 | • | |

| 品號 | 螺牙 | D | h | d | n-M×L | n | φb | c | 軸向負載能力 (KN) | 扭緊力矩 (max.Nm) | 鬆脫力矩 | 單價 |
|----------|--------|-----|----|-----|---------|---|----|------|----------------|------------------|--------|----|
| YSK-0074 | M 90×2 | 120 | 32 | 113 | 6-M6×22 | 6 | 8 | 105 | 680 | 8 | 656.9 | • |
| YSK-0076 | M 95×2 | 125 | | 118 | | | | 710 | 745.1 | | • | |
| YSK-0078 | M100×2 | 130 | | 123 | | | | 740 | 833.3 | | • | |
| YSK-0080 | M105×2 | 135 | | 128 | | | | 770 | 957.2 | | • | |
| YSK-0082 | M110×2 | 140 | 34 | 133 | 6-M6×25 | 6 | 8 | 125 | 800 | 8 | 1127.5 | • |
| YSK-0084 | M115×2 | 145 | | 137 | | | | 830 | 1242.3 | | • | |
| YSK-0086 | M120×2 | 155 | | 146 | | | | 860 | 1323.5 | | • | |
| YSK-0088 | M125×2 | 160 | | 150 | | | | 890 | 1389.4 | | • | |
| YSK-0090 | M130×2 | 165 | 36 | 155 | 8-M6×25 | 8 | 10 | 148 | 920 | 18 | 1421.5 | • |
| YSK-0092 | M140×2 | 180 | | 168 | | | | 980 | 1610.3 | | • | |
| YSK-0094 | M150×2 | 190 | | 178 | | | | 1040 | 1710 | | • | |
| YSK-0096 | M160×3 | 205 | | 190 | | | | 1100 | 1931.1 | | • | |
| YSK-0098 | M170×3 | 215 | 40 | 200 | 8-M8×30 | 8 | 10 | 193 | 1160 | 18 | 2052 | • |
| YSK-0100 | M180×3 | 230 | | 213 | | | | 1220 | 2214.1 | | • | |
| YSK-0102 | M190×3 | 240 | | 223 | | | | 1280 | 2596.4 | | • | |
| YSK-0104 | M200×3 | 245 | | 230 | | | | 1340 | 2731.2 | | • | |

Wa 注意

- 鎖定方式為利用鋼材本身的彈性,以軸向鎖固,強制鎖定,本產品特別針對工作環境劣、螺帽易於鬆脫的場合,其鎖定能力為傳統螺帽3倍以上,為其特異優點,YSK設計的鎖定方式,因為裝配上的誤差,故無法確保平面與螺紋的垂直偏擺為其缺點

· 1 Nm = 10.2 kgf.cm = 0.73 lb.ft

- 此商品包含螺絲

訂貨： 交期：

YSK-0002