



材質	硬度	螺紋精度	平面偏擺	平行度	同心度
SCM440	HRC48~52	ISO 4H 精密研磨	0.002mm	0.002mm	0.005mm

品號	螺牙	D	h	d	U x V	C	F	M x n	扭緊力矩 (max.Nm)	鬆脫力矩	單價
SBL-B-0002	M 20 x 1	38	16	33	M4 x 6	13	10	M 5 x 3	4.5	28.9	•
SBL-B-0004	M 20 x 1.5										
SBL-B-0006	M 25 x 1.5	45	18	40	M5 x 9	16	12	M 6 x 3	8	30.4	•
SBL-B-0008	M 30 x 1.5										
SBL-B-0010	M 35 x 1.5	58	20	47	M6 x 9	19	14	M 8 x 3	18	32.4	•
SBL-B-0012	M 40 x 1.5										
SBL-B-0014	M 45 x 1.5	70	22	52	M6 x 12	22	16	M 8 x 6	35	39.2	•
SBL-B-0016	M 50 x 1.5										
SBL-B-0018	M 55 x 2	80	24	59	M8 x 12	25	18	M 10 x 6	35	46.1	•
SBL-B-0020	M 60 x 2										
SBL-B-0022	M 65 x 2	105	26	64	M8 x 12	28	20	M 10 x 6	35	61.8	•
SBL-B-0024	M 70 x 2										
SBL-B-0026	M 75 x 2	110	28	68	M8 x 12	30	22	M 10 x 6	35	70.6	•
SBL-B-0028	M 80 x 2										
SBL-B-0030	M 85 x 2	120	30	73	M8 x 12	33	24	M 10 x 6	35	88.2	•
SBL-B-0032	M 90 x 2										
SBL-B-0034	M 95 x 2	130	32	78	M8 x 12	35	26	M 10 x 6	35	98	•
SBL-B-0036	M 100 x 2										
SBL-B-0038	M 105 x 2	145	34	84	M8 x 12	38	28	M 10 x 6	35	127.5	•
SBL-B-0040	M 110 x 2										
SBL-B-0042	M 115 x 2	155	36	90	M8 x 12	41	30	M 10 x 6	35	147.1	•
SBL-B-0044	M 120 x 2										
SBL-B-0046	M 125 x 2	165	38	96	M8 x 12	43	32	M 10 x 6	35	152	•
SBL-B-0048	M 130 x 2										
SBL-B-0050	M 135 x 2	175	40	102	M8 x 12	46	34	M 10 x 6	35	156.9	•
SBL-B-0052	M 140 x 2										
SBL-B-0054	M 145 x 2	180	42	108	M8 x 12	49	36	M 10 x 6	35	176.5	•
SBL-B-0056	M 150 x 2										

Wa) 注意

- 此型螺帽較SBL-A螺帽不同在於螺帽本身背面增加了可調整的平衡螺絲孔,可解決高速主軸在調校平衡的不方便和精度
- 本設計再配合公司所開發的消音螺絲將其平衡螺絲孔塞住,可完全降低高速所帶來的噪音問題
- 1 Nm = 10.2 kgf.cm = 0.73 lb.ft

訂貨: 交期:

SBL-B-0002