



材質	硬度	螺紋精度	平面偏擺	平行度	同心度
SCM440	HRC48~52	ISO 4H 精密研磨	0.002mm	0.002mm	0.005mm

品號	螺牙	D	h	d	U x V	C	F	M x n	扭緊力矩 (max.Nm)	鬆脫力矩	單價	
SBL-C-0002	M 20x1	38	16	33	M5x6	4	5	M 5x3	4.5	28.9	•	
SBL-C-0004	M 20x1.5							M 6x3				8
SBL-C-0006	M 25x1.5							M 8x3				
SBL-C-0008	M 30x1.5	45	18	40	M5x9	4.5	5	39.2	•			
SBL-C-0010	M 35x1.5									58	20	52
SBL-C-0012	M 40x1.5	70	22	64	M6x12	5.5	6	70.6	•			
SBL-C-0014	M 45x1.5									80	24	73
SBL-C-0016	M 50x1.5	85	26	78	M8x6	6	8	127.5	•			
SBL-C-0018	M 55x2									92	28	84
SBL-C-0020	M 60x2	98	30	90	M8x12	7	11	152	•			
SBL-C-0022	M 65x2									105	32	96
SBL-C-0024	M 70x2	110	34	102	M8x12	8	16	176.5	•			
SBL-C-0026	M 75x2									120	36	108
SBL-C-0028	M 80x2	125	38	113	M8x12	8	16	201	•			
SBL-C-0030	M 85x2									130	40	118
SBL-C-0032	M 90x2	135	42	125	M8x12	8	16	236.3	•			
SBL-C-0034	M 95x2									140	44	132
SBL-C-0036	M100x2	145	46	137	M8x12	8	16	268.1	•			
SBL-C-0038	M105x2									150	48	142
SBL-C-0040	M110x2	155	50	147	M8x12	8	16	289.2	•			
SBL-C-0042	M115x2									160	52	152
SBL-C-0044	M120x2	165	54	157	M8x12	8	16	352.9	•			
SBL-C-0046	M125x2									170	56	162
SBL-C-0048	M130x2	175	58	167	M8x12	8	16	436.3	•			
SBL-C-0050	M135x2									180	60	172
SBL-C-0052	M140x2	185	62	177	M8x12	8	16	480.4	•			
SBL-C-0054	M145x2									190	64	182
SBL-C-0056	M150x2	195	66	187	M8x12	8	16	480.4	•			

Wa) 注意

- 此型螺帽較SBL-A螺帽不同在於螺帽本身外圓增加了可調整的平衡螺絲孔，當主軸設計無法使用SBL-B型時，此型螺帽是最佳的代替品
- 本設計再配合公司所開發的消音螺絲將其平衡螺絲孔塞住，可完全降低高速所帶來的噪音問題
- 1 Nm = 10.2 kgf.cm = 0.73 lb.ft

訂貨： 交期： 天

SBL-C-0002