



材質	硬度	螺紋精度	平面偏擺	平行度	同心度
SCM440	HRC48~52	ISO 4H 精密研磨	0.002mm	0.002mm	0.005mm

品號	螺牙	D	h	d	U x V	C	F	M x n	扭緊力矩 (max.Nm)	鬆脫力矩	單價
SBL-E-0002	M 20 x 1	32	10	27	M5 x 6	5	3	M 5 x 3	4.5	24	•
SBL-E-0004	M 20 x 1.5										
SBL-E-0006	M 25 x 1.5	38	12	33	M5 x 6	6	4	M 6 x 3	8	26.5	•
SBL-E-0008	M 30 x 1.5										
SBL-E-0010	M 35 x 1.5	52	14	40	M5 x 9	7	5	M 6 x 3	8	34.3	•
SBL-E-0012	M 40 x 1.5										
SBL-E-0014	M 45 x 1.5	65	16	52	M6 x 9	8	6	M 8 x 6	18	36.3	•
SBL-E-0016	M 50 x 1.5										
SBL-E-0018	M 55 x 2	75	18	59	M6 x 12	9	8	M 8 x 6	18	56.9	•
SBL-E-0020	M 60 x 2										
SBL-E-0022	M 65 x 2	85	20	64	M6 x 12	10	9	M 8 x 6	18	63.7	•
SBL-E-0024	M 70 x 2										
SBL-E-0026	M 75 x 2	92	22	68	M6 x 12	11	11	M 8 x 6	18	68.6	•
SBL-E-0028	M 80 x 2										
SBL-E-0030	M 85 x 2	98	24	73	M6 x 12	12	11	M 8 x 6	18	96.1	•
SBL-E-0032	M 90 x 2										
SBL-E-0034	M 95 x 2	105	26	78	M6 x 12	13	14	M 10 x 6	35	112.7	•
SBL-E-0036	M 100 x 2										
SBL-E-0038	M 105 x 2	110	28	84	M8 x 12	14	16	M 10 x 6	35	137.3	•
SBL-E-0040	M 110 x 2										
SBL-E-0042	M 115 x 2	120	30	90	M8 x 12	15	16	M 10 x 6	35	145.1	•
SBL-E-0044	M 120 x 2										
SBL-E-0046	M 125 x 2	125	32	96	M8 x 12	16	16	M 10 x 6	35	149	•
SBL-E-0048	M 130 x 2										
SBL-E-0050	M 135 x 2	130	34	102	M8 x 12	17	16	M 10 x 6	35	168.6	•
SBL-E-0052	M 140 x 2										
SBL-E-0054	M 145 x 2	135	36	108	M8 x 12	18	16	M 10 x 6	35	178.4	•
SBL-E-0056	M 150 x 2										

Wa) 注意

- 此型螺帽不同於 SBL-D 型螺帽，在於其平衡螺絲孔位於螺帽外圓，當平衡調整無法從背面調整時，此型為最佳的代替品，配合消音螺絲，可降低高速所帶來的噪音問題

• 1 Nm = 10.2 kgf.cm = 0.73 lb.ft

訂貨： 交期：

SBL-E-0002