



材質	處理
高力黃銅	埋入MOS ₂

Type	品號		外徑		F	e 0 -0.1	L												
	d	公差	D	公差			10	15	20	25	30	35	40	50	60	67.5	80	100	
SPF	10	+0.040 +0.025	14		22	2	△	△	△										
	12		18	+0.034 +0.023	25		△	△	△										
	13		19		26		△	△	△										
	14	+0.050 +0.032	20		27	3		△	△										
	15		21	+0.041 +0.028	28			△	△	△	△								
	16		22		29			△	△	△	△								
	20		30		40			△	△	△	△		△						
	25	+0.061 +0.040	35		45			△	△	△	△		△						
	30		40	+0.050 +0.034	50				△	△	△	△	△	△					
	31.5		45		60	5			△		△		△	△					
	35	+0.075 +0.050	50		65				△		△		△	△					
	40		55		70					△		△	△	△					
	45		60	+0.060 +0.041	75					△		△	△	△					
	50		65		80						△		△	△					
	55		75	+0.062 +0.043	90							△	△	△			△		
	60	+0.090 +0.060	85		85	7.5									△				
	63		90	+0.073 +0.051	105											△			
	70		90		110												△		
	75		100		120													△	
	80		110	+0.076 +0.054	130	10												△	
90	+0.107 +0.072	120		150													△		
100		140	+0.088 +0.063	170													△		
120																	△		

Wa 注意

· 軸配合公差：一般高荷重用d8，一般輕荷重用e7，高精度用f7

訂貨：品號 - d L 交期：3~20天

SPF - 10 10