



Inch sizes available

3 Identification no.

- 1 Without vent hole
- 2 With vent hole

1 d_1	2 d_2		d_3 Vent hole	d_4	$l_1 \pm 0,5$	l_2	l_3	s	t min.
22	G 3/8	M 16 x 1,5	2	M 5	26	8	15	5	8
26	G 1/2	M 20 x 1,5	2	M 5	27,5	8,5	16	5	8
32	G 3/4	M 26 x 1,5	2	M 5	29	9	17	6	8
40	G 1	-	2	M 5	32,5	11	18	7	8

Specification

- Aluminum
 - Powder coated
 - Black, RAL 9005, textured finish ● **SW**
 - Plain, tumbled ○ **BL**
- **GN 441**
 - Temperature resistant up to 100 °C
 - Seal rubber NBR (Perbunan®)
- **GN 442**
 - Temperature resistant up to 200 °C
 - Seal rubber FPM (Viton®)
 - Identification by not black finish of the seal
- *Elastomer Characteristics* → Page 2158
- **RoHS**

On request

- Version with dipstick

Information

Threaded plugs GN 441 / GN 442 with the external diameter d_1 match the screw-in holes for DIN 3852 pipe bolt connections.

The sealing ring is embedded in a radial recess on the flat side. This prevents the seal from being lost or squeezed out during tightening.

see also...

- *Threaded Plugs GN 741 / GN 742 (with External Hexagon)* → Page 1590
- *Plugs GN 548.1 (Plastic)* → Page 1601

How to order (100 °C)

1	d_1
2	d_2
3	Identification no.
4	Finish

GN 441-22-M16x1,5-1-BL

How to order (200 °C)

1	d_1
2	d_2
3	Identification no.
4	Finish

GN 442-40-G1-1-SW