


RoHS

齒輪形狀：B



TYPE	材質	處理	壓力角
HCWGT	S45C	-	20°
HCWGTT		染黑	
HCWGTH		無電鍍	
HCWGP	SUS304	-	


標準軸孔



TYPE	M 模數	Y 齒輪形狀	T 齒數	B 厚度	d 指定單位1mm	Dp 基準圓直徑	D 齒頂圓直徑	DH	L				
(S45C) HCWGT HCWGTT HCWGTH	1.0	B	15	10	6~10	15	17	12	20				
			16		6~12	16	18	13					
			18		6~10	18	20	15					
			19			19	21	16					
			20		20	22	17						
			22		6~12	22	24	19					
			24			24	26	21					
			25			25	27	22					
			26		6~15	26	28	23					
			28		8~17	28	30	25					
			30			30	32	27					
			(SUS304) HCWGP		1.0	B	32	8~18		32	34	29	30
							34			34	36	30	
							35	8~20		35	37	32	
36	36	38											
40	40	42		36									
42	42	44		38									
45	45	47		42									
48	8~30	48		50			45						
50	10~32	50		52			46						
55		55		57			50						
60		60	62	55									
70	10~35	70	72	65									
75		75	77	70									
80	10~42	80	82	74									

追加工

	Alteration	Code	Spec.
軸孔追加工		AT	鍵槽孔
		BT	圓孔+攻牙
		CT	鍵槽孔+攻牙
止付螺絲孔追加工		BT90 CT90	止付螺絲孔90° 增加1孔
		BT120 CT120	止付螺絲孔120° 增加1孔



對照表

d H7	M
4~8	M3
9~12	M4
13~17	M5
18~30	M6
31~45	M8
46~60	M10

PS. 備註

- 熱處理需求歡迎洽詢
- 接受圖面詢價，可依圖面生產
- 追加工詳細請參閱P.503

訂貨：TYPE - M - Y - T - B - d - (追加工 Code)

HCWGT - 1.0 - B - 24 - 10 - 8

HCWGTH - 1.0 - B - 42 - 10 - 10 - AT

HCWGTH - 1.0 - B - 50 - 10 - 16 - BT90

交期：8 天 S45C

12 天 SUS304