


RoHS

齒輪形狀：A



TYPE	材質	處理	壓力角
HCWGT	S45C	-	20°
HCWGTT		染黑	
HCWGTH		無電解鍍	
HCWGP	SUS304	-	

標準軸孔



圓孔

TYPE	M 模數	Y 齒輪形狀	T 齒數	B 厚度	d 指定單位1mm	Dp 基準圓直徑	D 齒頂圓直徑			
(S45C) HCWGT HCWGTT HCWGTH	1.5	A	15	15	8~12	22.5	25.5			
			16			24	27			
			18		8~13	27	30			
			19		8~15	28.5	31.5			
			20		8~16	30	33			
			22		8~17	33	36			
			24		8~20	36	39			
			25			37.5	40.5			
			26		8~22	39	42			
			28		8~23	42	45			
			30		8~24	45	48			
			32			48	51			
			(SUS304) HCWGP				34	8~28	51	54
							35		52.5	55.5
							36	10~28	54	57
40	10~31	60		63						
42		63		66						
45	12~31	67.5		70.5						
48	12~35	72		75						
50		75		78						
55		82.5		85.5						
60	12~38	90		93						
70	12~45	105	108							
75		112.5	115.5							
80		120	123							

PS. 備註

- 熱處理需求歡迎洽詢
- 接受圖面詢價，可依圖面生產
- 軸孔追加加工詳細請參閱P.503

軸孔追加加工

Alteration	Code	Spec.
	AT	鍵槽孔

訂貨：TYPE - M - Y - T - B - d - (追加加工 Code)

HCWGT - 1.5 - A - 19 - 15 - 8

HCWGTH - 1.5 - A - 30 - 15 - 10 - AT

交期：8天 S45C

12天 SUS304