


(RoHS)

齒輪形狀：B



| TYPE   | 材質     | 處理   | 壓力角 |
|--------|--------|------|-----|
| HCWGT  | S45C   | -    | 20° |
| HCWGTT | S45C   | 染黑   |     |
| HCWGTH | S45C   | 無電解鍍 |     |
| HCWGP  | SUS304 | -    |     |

標準軸孔




圓孔

| TYPE                                | M<br>模數 | Y<br>齒輪形狀 | T<br>齒數 | B<br>厚度 | d<br>指定單位1mm | Dp<br>基準圓直徑 | D<br>齒頂圓直徑 | DH | L  |  |
|-------------------------------------|---------|-----------|---------|---------|--------------|-------------|------------|----|----|--|
| (S45C)<br>HCWGT<br>HCWGTT<br>HCWGTH | 1.5     | B         | 15      | 15      | 8~12         | 22.5        | 25.5       | 18 | 28 |  |
|                                     |         |           | 16      |         | 24           | 27          | 30         | 20 |    |  |
|                                     |         |           | 18      |         | 8~13         | 27          | 30         | 23 |    |  |
|                                     |         |           | 19      |         | 8~15         | 28.5        | 31.5       | 24 |    |  |
|                                     |         |           | 20      |         | 8~16         | 30          | 33         | 26 |    |  |
|                                     |         |           | 22      |         | 8~17         | 33          | 36         | 28 |    |  |
|                                     |         |           | 24      |         | 8~20         | 36          | 39         | 32 |    |  |
|                                     |         |           | 25      |         |              | 37.5        | 40.5       | 33 |    |  |
|                                     |         |           | 26      |         | 8~22         | 39          | 42         | 35 |    |  |
|                                     |         |           | 28      |         | 8~23         | 42          | 45         | 38 |    |  |
|                                     |         |           | 30      |         | 8~24         | 45          | 48         | 40 |    |  |
|                                     |         |           | 32      |         | 8~28         | 48          | 51         | 44 |    |  |
|                                     |         |           | 34      |         |              | 51          | 54         | 46 |    |  |
|                                     |         |           | 35      |         | 10~28        | 52.5        | 55.5       | 48 |    |  |
|                                     |         |           | 36      |         |              | 54          | 57         | 50 |    |  |
|                                     |         |           | 40      |         | 10~31        | 60          | 63         | 54 |    |  |
|                                     |         |           | 42      |         |              | 63          | 66         | 58 |    |  |
|                                     |         |           | 45      |         | 12~31        | 67.5        | 70.5       | 62 |    |  |
|                                     |         |           | 48      |         |              | 72          | 75         |    |    |  |
|                                     |         |           | 50      |         | 12~35        | 75          | 78         | 65 |    |  |
|                                     |         |           | 55      |         |              | 82.5        | 85.5       |    |    |  |
|                                     |         |           | 60      |         | 12~38        | 90          | 93         | 65 |    |  |
|                                     |         |           | 70      |         |              | 105         | 108        |    |    |  |
|                                     |         |           | 75      |         | 12~45        | 112.5       | 115.5      |    |    |  |
|                                     |         |           | 80      |         |              | 120         | 123        | 70 |    |  |

追加工

| Alteration                           | Code  | Spec.     |
|--------------------------------------|-------|-----------|
| 軸<br>孔<br>追<br>加<br>工                | AT    | 鍵槽孔       |
|                                      | BT    | 圓孔+攻牙     |
|                                      | CT    | 鍵槽孔+攻牙    |
| 止<br>付<br>螺<br>絲<br>孔<br>追<br>加<br>工 | BT90  | 止付螺絲孔90°  |
|                                      | CT90  | 增加1孔      |
| 止<br>付<br>螺<br>絲<br>孔<br>追<br>加<br>工 | BT120 | 止付螺絲孔120° |
|                                      | CT120 | 增加1孔      |



| d<br>H7 | M   |
|---------|-----|
| 4~8     | M3  |
| 9~12    | M4  |
| 13~17   | M5  |
| 18~30   | M6  |
| 31~45   | M8  |
| 46~60   | M10 |

PS 備註

- 热處理需求歡迎洽詢
- 接受圖面詢價，可依圖面生產
- 追加工詳細請參閱P.503

訂貨： TYPE -  M -  Y -  T -  B -  d -  (追加工 Code)

HCWGT - 1.5 - B - 24 - 15 - 8

HCWGTH - 1.5 - B - 42 - 15 - 10 - AT

HCWGTH - 1.5 - B - 50 - 15 - 16 - BT90

交期： 8 天 S45C

12 天 SUS304